

Description

IP66, Class I. Class II on request. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® gasket. Safety glass lens. Two cable entries. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board.

Other standardised housing lengths, 250 mm and 300 mm available on request.

Optional 2200 K version available. To be specified at time of ordering.

Specifications

Material description

| | | | | |
|--------------------|--------------------------------|----------------------------------|-----------------------------------|---------------------------------|
| Colours | RAL9004 Signal black | RAL9007 Grey aluminium | RAL7016 Anthracite grey | RAL9016 Traffic white |
| Ingress protection | IP66 | | | |
| Impact resistance | IK07 | | | |

Electrical description

| | |
|-------------------|---|
| Power supply | 220-240V / 50-60 Hz |
| Driver / Ballast | Integral EC electronic converter in thermally separated compartment |
| Energy efficiency | C-D (Light source) |

Additional information

| | |
|----------|-------------------------------------|
| Lifetime | T _a =25° L90B10 > 90000h |
|----------|-------------------------------------|

Options**Light distribution Colour temperature Nominal Watt**

[B]



2700K

12 W




[M]



3000K



[EE]







4000K



[EES]

Configurations

| Light distribution | Part ID | Light source | Rated lumens | Rated input power | CRI | |
|---|----------|-----------------|-----------------|-------------------|------|----|
|  | 134-2077 | LED-6/12W/2700K | 1070 lm | 12 W | 80 | |
| | 134-2078 | LED-6/12W/3000K | 1149.2 lm | 12 W | 80 | |
| | 134-2079 | LED-6/12W/4000K | 1228.5 lm | 12 W | 80 | |
| [B] | | | | | | |
|  | 134-2083 | LED-6/12W/2700K | 1347.7 lm | 12 W | 80 | |
| | 134-2084 | LED-6/12W/3000K | 1447.6 lm | 12 W | 80 | |
| | 134-2085 | LED-6/12W/4000K | 1547.4 lm | 12 W | 80 | |
| [EE] | | | | | | |
|  | 134-2086 | LED-6/12W/2700K | 1424 lm | 12 W | 80 | |
| | 134-2087 | LED-6/12W/3000K | 1529.5 lm | 12 W | 80 | |
| | 134-2088 | LED-6/12W/4000K | 1635 lm | 12 W | 80 | |
| [EES] | | | | | | |
|  | 134-2080 | LED-6/12W/2700K | 1201.1 lm | 12 W | 80 | |
| | 134-2080 | LED-6/12W/2700K | 1201.1 lm | 12 W | 80 | |
| | 134-2081 | LED-6/12W/3000K | 1290.1 lm | 12 W | 80 | |
| | 134-2081 | LED-6/12W/3000K | 1290.1 lm | 12 W | 80 | |
| | [M] | 134-2082 | LED-6/12W/4000K | 1379 lm | 12 W | 80 |
| | 134-2082 | LED-6/12W/4000K | 1379 lm | 12 W | 80 | |