

### Description

IP66, Class I. Class II on request. IK07. Marine-grade, all aluminium construction. 5CE superior corrosion protection including PCS hardware. Silicone CCG® gasket. Safety glass lens. Two cable entries. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. Factory installed LED circuit board. The luminaire is factory-sealed and does not need to be opened during installation.

Other standardised housing lengths, 190 mm and 250 mm available on request.

Optional 2200 K version available. To be specified at time of ordering.

## Specifications

### Material description

Colours	<b>RAL9004</b>	<b>RAL9006</b>	<b>RAL9007</b>	<b>RAL7016</b>
	Signal black	White aluminium	Grey aluminium	Anthracite grey
	<b>RAL9016</b>			
	Traffic white			
Ingress protection	IP66			
Impact resistance	IK07			

### Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Standard. Optional DALI version available. To be specified at time of ordering.

### Additional information

Lifetime	Ta=25° L90B10 > 90000h
----------	------------------------

## Options

### Light distribution



[B] symmetric, wide beam



[M] symmetric, medium beam



[EE] symmetric, very narrow beam



[EES] symmetric, very narrow beam, sharp cut-off


### Colour temperature



2700K



3000K







4000K

### Nominal Watt

48 W

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	134-2246	LED-24/48W/2700K	4916.1 lm	48 W	80
	134-2247	LED-24/48W/3000K	5280.3 lm	48 W	80
	134-2248	LED-24/48W/4000K	5644.5 lm	48 W	80
[B] symmetric, wide beam					
	134-2252	LED-24/48W/2700K	5546.8 lm	48 W	80
	134-2253	LED-24/48W/3000K	5957.7 lm	48 W	80
	134-2254	LED-24/48W/4000K	6368.6 lm	48 W	80
[EE] symmetric, very narrow beam					
	134-2255	LED-24/48W/2700K	5785.2 lm	48 W	80
	134-2256	LED-24/48W/3000K	6213.7 lm	48 W	80
	134-2257	LED-24/48W/4000K	6642.2 lm	48 W	80
[EES] symmetric, very narrow beam, sharp cut-off					
	134-2249	LED-24/48W/2700K	5378.5 lm	48 W	80
	134-2250	LED-24/48W/3000K	5776.9 lm	48 W	80
	134-2251	LED-24/48W/4000K	6175.3 lm	48 W	80
[M] symmetric, medium beam					