

Description

IP66, Class I. Class II on request. IK07. Marine-grade, all aluminium construction. 5CE superior corrosion protection including PCS hardware. Silicone CCG® gasket. Safety glass lens. Two cable entries. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. Factory installed LED circuit board. The luminaire is factory-sealed and does not need to be opened during installation.

Other standardised housing lengths, 190 mm and 250 mm available on request.

Optional 2200 K version available. To be specified at time of ordering.

Specifications

Material description

Colours	RAL9004	RAL9006	RAL9007	RAL7016
	Signal black	White aluminium	Grey aluminium	Anthracite grey
	RAL9016			
	Traffic white			
Ingress protection	IP66			
Impact resistance	IK07			

Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Standard. Optional DALI version available. To be specified at time of ordering.

Additional information

Lifetime	Ta=25° L90B10 > 90000h
----------	------------------------

Options

Light distribution Colour temperature Nominal Watt



[B]



2700K

48 W




[M]



3000K



[EE]







4000K



[EES]

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	134-2246	LED-24/48W/2700K	4916.1 lm	48 W	80
	134-2247	LED-24/48W/3000K	5280.3 lm	48 W	80
	134-2248	LED-24/48W/4000K	5644.5 lm	48 W	80
[B]					
	134-2252	LED-24/48W/2700K	5546.8 lm	48 W	80
	134-2253	LED-24/48W/3000K	5957.7 lm	48 W	80
	134-2254	LED-24/48W/4000K	6368.6 lm	48 W	80
[EE]					
	134-2255	LED-24/48W/2700K	5785.2 lm	48 W	80
	134-2256	LED-24/48W/3000K	6213.7 lm	48 W	80
	134-2257	LED-24/48W/4000K	6642.2 lm	48 W	80
[EES]					
	134-2249	LED-24/48W/2700K	5378.5 lm	48 W	80
	134-2249	LED-24/48W/2700K	5378.5 lm	48 W	80
	134-2250	LED-24/48W/3000K	5776.9 lm	48 W	80
	134-2250	LED-24/48W/3000K	5776.9 lm	48 W	80
	134-2251	LED-24/48W/4000K	6175.3 lm	48 W	80
	134-2251	LED-24/48W/4000K	6175.3 lm	48 W	80
[M]					