

Description

IP66, Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Two cable entries. Integral driver, thermally separated. CAD-optimized optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board. 0-10V Dimming comes standard with luminaire.

Optional 2200 K version available, to be specified at time of ordering.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX - 9004 (Black)
+ XXX-XXXX (Accessory 1)

For DarkSky compliant configurations of this product, please find the spec sheet and DarkSky certificate in the library.

Specifications

Material description

Colors	RAL9004 Signal black	RAL9007 Grey aluminium	RAL9016 Traffic white	RAL8019 Grey brown
Ingress protection	IP66			
Impact resistance	IK07			








Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter in thermally-separated compartment





Additional information

Listings	Contact WE-EF USA for ETL/UL certification status.
Lifetime	Ta=25°/40° L90B10 > 90000h

Options

Light distribution	Color temperature	Nominal Watt
 [B]	 2700K	48 W
 [M]	 3000K	
 [EE]	 4000K	
 [EES]		

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI	
	134-2246	LED-24/48W/2700K	4916.1 lm	48 W	80	
	134-2247	LED-24/48W/3000K	5280.3 lm	48 W	80	
	134-2248	LED-24/48W/4000K	5644.5 lm	48 W	80	
[B]						
	134-2252	LED-24/48W/2700K	5546.8 lm	48 W	80	
	134-2253	LED-24/48W/3000K	5957.7 lm	48 W	80	
	134-2254	LED-24/48W/4000K	6368.6 lm	48 W	80	
[EE]						
	134-2255	LED-24/48W/2700K	5785.2 lm	48 W	80	
	134-2256	LED-24/48W/3000K	6213.7 lm	48 W	80	
	134-2257	LED-24/48W/4000K	6642.2 lm	48 W	80	
[EES]						
	134-2249	LED-24/48W/2700K	5378.5 lm	48 W	80	
	134-2249	LED-24/48W/2700K	5378.5 lm	48 W	80	
	134-2250	LED-24/48W/3000K	5776.9 lm	48 W	80	
	134-2250	LED-24/48W/3000K	5776.9 lm	48 W	80	
	[M]	134-2251	LED-24/48W/4000K	6175.3 lm	48 W	80
	134-2251	LED-24/48W/4000K	6175.3 lm	48 W	80	