**Description**

IP66, Class I. IK07. Marine-grade, all aluminium construction. 5CE superior corrosion protection + primer including PCS hardware. Silicone CCG® gasket. Safety glass lens. Two cable entries. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. Factory installed LED circuit board. Tunable White Technology. The luminaire is factory-sealed and does not need to be opened during installation.

Other standardised housing lengths, 190 mm and 250 mm available on request.

## Specifications

### Material description

---

Colours

**RAL9004**

Signal black

**RAL9006**

White aluminium

**RAL9007**

Grey aluminium

Ingress protection IP66

Impact resistance IK07

Corrosion resistance 5CE+Primer

---

### Electrical description

---

Energy efficiency D (Light source)

---

### Additional information

---

Lifetime Ta=40° L90B10 > 90000h

---

**Options**

**Light distribution**

**Colour temperature**

**Nominal Watt**



[B] symmetric, wide beam

2200-6000K

42 W






[M] symmetric, medium beam



[E] symmetric, narrow beam

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [B] symmetric, wide beam	134-2258	LED-2/42W/2200-6000K	3993.5 lm	42 W	80
 [E] symmetric, narrow beam	134-2260	LED-2/42W/2200-6000K	4406.3 lm	42 W	80
 [M] symmetric, medium beam	134-2259	LED-2/42W/2200-6000K	4237.4 lm	42 W	80