

Description

IP66, Class I. Class II on request. IK07. Marine-grade, all aluminium construction. 5CE superior corrosion protection including PCS hardware. Silicone CCG[®] gasket. Safety glass lens. Two cable entries. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. Factory installed LED circuit board. Tunable White Technology. The luminaire is factory-sealed and does not need to be opened during installation.

Other standardised housing lengths, 190 mm and 250 mm available on request.

Specifications

Material description

Colours	RAL9004 Signal black	RAL9007 Grey aluminium	RAL7016 Anthracite grey	RAL9016 Traffic white
Ingress protection	IP66			
Impact resistance	IK07			

Electrical description

Energy efficiency	D (Light source)
-------------------	------------------

Additional information

Lifetime	Ta=25° L90B10 > 90000h
----------	------------------------

Options**Light distribution****Colour temperature****Nominal Watt**

[B] symmetric, wide beam

2200-6000K

42 W






[M] symmetric, medium beam



[E] symmetric, narrow beam

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 <p>[B] symmetric, wide beam</p>	134-2258	LED-2/42W/2200-6000K	3993.5 lm	42 W	80
 <p>[E] symmetric, narrow beam</p>	134-2260	LED-2/42W/2200-6000K	4406.3 lm	42 W	80
 <p>[M] symmetric, medium beam</p>	134-2259	LED-2/42W/2200-6000K	4237.4 lm	42 W	80