

Description

IP66, Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Two cable entries. Integral driver in thermally separated compartment. CAD-optimized optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board. Tunable White technology. DMX interface.

Optional 2200 K version available, to be specified at time of ordering.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX - 9004 (Black)
+ XXX-XXXX (Accessory 1)

Specifications

Material description

Colors	RAL9004 Signal black	RAL9007 Grey aluminium	RAL9016 Traffic white	RAL8019 Grey brown
Ingress protection	IP66			
Impact resistance	IK07			




Electrical description

Driver / Ballast	DMX
Energy efficiency	D (Light source)




Additional information

Listings	Contact WE-EF USA for ETL/UL certification status.
Lifetime	Ta=25°/40° L90B10 > 90000h

Options

Light distribution	Color temperature	Nominal Watt
 [B] symmetric, wide beam	2200-6000K	42 W
 [M] symmetric, medium beam		
 [E] symmetric, narrow beam		

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 <p>[B] symmetric, wide beam</p>	134-2258	LED-2/42W/2200-6000K	3993.5 lm	42 W	80
 <p>[E] symmetric, narrow beam</p>	134-2260	LED-2/42W/2200-6000K	4406.3 lm	42 W	80
 <p>[M] symmetric, medium beam</p>	134-2259	LED-2/42W/2200-6000K	4237.4 lm	42 W	80