

#### Description

IP66, Class I. Class II on request. IK07. Marine-grade, all aluminium construction. 5CE superior corrosion protection including PCS hardware. Silicone CCG<sup>®</sup> gasket. Safety glass lens. Two cable entries. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. Factory installed LED circuit board. Tunable White Technology. The luminaire is factory-sealed and does not need to be opened during installation.

Other standardised housing lengths, 190 mm and 250 mm available on request.

## Specifications

### Material description

Colours	<b>RAL9004</b>	<b>RAL9006</b>	<b>RAL9007</b>	<b>RAL7016</b>
	Signal black	White aluminium	Grey aluminium	Anthracite grey
	<b>RAL9016</b>			
	Traffic white			
Ingress protection	IP66			
Impact resistance	IK07			

### Electrical description

Energy efficiency	D (Light source)
-------------------	------------------

### Additional information

Lifetime	Ta=25° L90B10 > 90000h
----------	------------------------

**Options**

**Light distribution**    **Colour temperature**    **Nominal Watt**



[B]

2200-6000K

42 W






[M]



[E]

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [B]	134-2258	LED-2/42W/2200-6000K	3993.5 lm	42 W	80
 [E]	134-2260	LED-2/42W/2200-6000K	4406.3 lm	42 W	80
 [M]	134-2259	LED-2/42W/2200-6000K	4237.4 lm	42 W	80