

#### Description

IP66, Class I. IK07. Marine-grade, all aluminium construction. 5CE superior corrosion protection + primer including PCS hardware. Silicone CCG® gasket. Safety glass lens. Two cable entries. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. Factory installed LED circuit board. Tunable White Technology. The luminaire is factory-sealed and does not need to be opened during installation.

Other standardised housing lengths, 190 mm and 250 mm available on request.

## Specifications

### Material description

---

Colours	<b>RAL9004</b> Signal black	<b>RAL9006</b> White aluminium	<b>RAL9007</b> Grey aluminium
Ingress protection	IP66		
Impact resistance	IK07		
Corrosion resistance	5CE+Primer		

---

### Electrical description

---

Energy efficiency	D (Light source)
-------------------	------------------

---

### Additional information

---

Lifetime	Ta=40° L90B10 > 90000h
----------	------------------------

---

**Options**

**Light distribution**    **Colour temperature**    **Nominal Watt**



[B]

2200-6000K

42 W






[M]



[E]

### Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 <p>[B]</p>	134-2258	LED-2/42W/2200-6000K	3993.5 lm	42 W	80
 <p>[E]</p>	134-2260	LED-2/42W/2200-6000K	4406.3 lm	42 W	80
 <p>[M]</p>	134-2259	LED-2/42W/2200-6000K	4237.4 lm	42 W	80