

### Description

IP65. Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens, hinged. CAD-optimized optics for superior illumination and glare control. Integral driver in thermally separated compartment. OLC® One LED Concept. Factory-installed LED circuit board. 0-10V Dimming comes standard with luminaire. Frame with safety catch.

Suitable for installation over recessed junction box.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)  
+ XXX-XXXX (Accessory 1)

## Specifications

### Material description

Body	Marine-grade die-cast aluminium alloy			
Lens	Safety glass lens, hinged			
Colors	<b>RAL9004</b> Signal black	<b>RAL9016</b> Traffic white	<b>RAL8019</b> Grey brown	<b>RAL9007</b> Grey aluminium
Gasket	Silicone rubber gasket			
Fasteners	PCS Polymer Coated Stainless Steel Hardware			
Ingress protection	IP65			
Impact resistance	IK07			
Corrosion resistance	5CE			

### Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Integral EC electronic converter in thermally-separated compartment
Surge protection	1/2 kV
Energy efficiency	C-D (Light source)

### Additional information

Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.
Lifetime	Ta=25°/40° L90B10 > 90000h

**Options**

**Light distribution**

**Color temperature**

**Nominal Watt**



[W] bi-symmetric, wide beam

0 W



[VN] symmetric, very narrow beam







[VNS] symmetric, very narrow beam, sharp cut-off



[M] symmetric, medium beam

## Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
	134-1429_us		3205.4 lm	0 W	80
[M] symmetric, medium beam					
	134-1426_us		2883.7 lm	0 W	80
[VN] symmetric, very narrow beam					
	134-1427_us		3077.9 lm	0 W	80
	134-1431_us		3290.2 lm	0 W	80
[VNS] symmetric, very narrow beam, sharp cut-off					
	134-1424_us		2709.2 lm	0 W	80
	134-1428_us		2896 lm	0 W	80
[W] bi-symmetric, wide beam					