**Description**

IP65, Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Silicone rubber gasket. Safety glass lens, hinged. Frame with safety catch. Two cable entries. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. OLC_R_One LED Concept. Factory installed LED circuit board.

2700 K option available on request.

Specifications

Material description

Body	Marine-grade die-cast aluminium alloy						
Lens	Safety glass lens, hinged						
Colours	<table><tr><td>RAL9004</td><td>RAL9006</td><td>RAL9007</td></tr><tr><td>Signal black</td><td>White aluminium</td><td>Grey aluminium</td></tr></table>	RAL9004	RAL9006	RAL9007	Signal black	White aluminium	Grey aluminium
RAL9004	RAL9006	RAL9007					
Signal black	White aluminium	Grey aluminium					
Gasket	Silicone rubber gasket						
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)						
Ingress protection	IP65						
Impact resistance	IK07						
Corrosion resistance	5CE+Primer						

Electrical description

Power supply	230V / 50 Hz
Driver / Ballast	Integral EC electronic converter in thermally-separated compartment
Surge protection	1/2 kV
Energy efficiency	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details.

Additional information

Lifetime	Ta=40° L90B10 > 90000h
----------	------------------------

Options**Light distribution Colour temperature Nominal Watt**

[B]




3000K

24 W



[M]



4000K



[EE]







2700K



[EES]

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	134-1949	LED-12/24W/2700K	2522.3 lm	24 W	80
	134-1424	LED-12/24W/3000K	2709.2 lm	24 W	80
	134-1428	LED-12/24W/4000K	2896 lm	24 W	80
[B]					
	134-1951	LED-12/24W/2700K	2684.8 lm	24 W	80
	134-1951	LED-12/24W/2700K	2684.8 lm	24 W	80
	134-1426	LED-12/24W/3000K	2883.7 lm	24 W	80
	134-1426	LED-12/24W/3000K	2883.7 lm	24 W	80
	134-1430	LED-12/24W/4000K	3082.5 lm	24 W	80
	134-1430	LED-12/24W/4000K	3082.5 lm	24 W	80
[EE]					
	134-1952	LED-12/24W/2700K	2865.6 lm	24 W	80
	134-1952	LED-12/24W/2700K	2865.6 lm	24 W	80
	134-1427	LED-12/24W/3000K	3077.9 lm	24 W	80
	134-1427	LED-12/24W/3000K	3077.9 lm	24 W	80
	134-1431	LED-12/24W/4000K	3290.2 lm	24 W	80
	134-1431	LED-12/24W/4000K	3290.2 lm	24 W	80
[EES]					
	134-1950	LED-12/24W/2700K	2791.8 lm	24 W	80
	134-1950	LED-12/24W/2700K	2791.8 lm	24 W	80
	134-1425	LED-12/24W/3000K	2998.6 lm	24 W	80
	134-1425	LED-12/24W/3000K	2998.6 lm	24 W	80
	134-1429	LED-12/24W/4000K	3205.4 lm	24 W	80
	134-1429	LED-12/24W/4000K	3205.4 lm	24 W	80
[M]					