

Description

IP65. Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens, hinged. CAD-optimized optics for superior illumination and glare control. Integral driver in thermally separated compartment. OLC® One LED Concept. Factory-installed LED circuit board. 0-10V Dimming comes standard with luminaire. Frame with safety catch.

Suitable for installation over recessed junction box.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)
+ XXX-XXXX (Accessory 1)

Specifications

Material description

Body	Marine-grade die-cast aluminium alloy			
Lens	Safety glass lens, hinged			
Colors	RAL9004 Signal black	RAL9016 Traffic white	RAL8019 Grey brown	RAL9007 Grey aluminium
Gasket	Silicone rubber gasket			
Fasteners	PCS Polymer Coated Stainless Steel Hardware			
Ingress protection	IP65			
Impact resistance	IK07			
Corrosion resistance	5CE			







Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Integral EC electronic converter in thermally-separated compartment
Surge protection	6/6 kV
Energy efficiency	C-D (Light source)





Additional information

Diameter (inches)	9.84
Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.
Lifetime	Ta=25°/40° L90B10 > 90000h

Options

Light distribution	Color temperature	Nominal Watt
 [B]	 3000K	48 W
 [M]	 4000K	
 [EE]		
 [EES]		

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
	134-1432	LED-24/48W/3000K	5388.5 lm	48 W	80
	134-1436	LED-24/48W/4000K	5760.1 lm	48 W	80
[B]					
	134-1434	LED-24/48W/3000K	5986.1 lm	48 W	80
	134-1438	LED-24/48W/4000K	6398.9 lm	48 W	80
[EE]					
	134-1435	LED-24/48W/3000K	6442.7 lm	48 W	80
	134-1439	LED-24/48W/4000K	6887 lm	48 W	80
[EES]					
	134-1433	LED-24/48W/3000K	6047.2 lm	48 W	80
	134-1433	LED-24/48W/3000K	6047.2 lm	48 W	80
	134-1433	LED-24/48W/3000K	6047.2 lm	48 W	80
	134-1437	LED-24/48W/4000K	6464.2 lm	48 W	80
	134-1437	LED-24/48W/4000K	6464.2 lm	48 W	80
	134-1437	LED-24/48W/4000K	6464.2 lm	48 W	80
[M]					