

### Description

IP66, Class I. Class II on request. IK07. Marine-grade, all aluminium construction. 5CE superior corrosion protection including PCS hardware. Silicone CCG<sup>®</sup> gasket. Safety glass lens. Two cable entries. Ceiling mount through canopy. Cable suspension 0.5 - 1.5 m. To be specified at time at ordering. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. OLC<sup>®</sup> One LED Concept. Factory installed LED circuit board.

Optional 2200 K version available. To be specified at time of ordering.

## Specifications

### Material description

Colours	<b>RAL9004</b>	<b>RAL9006</b>	<b>RAL9007</b>	<b>RAL7016</b>
	Signal black	White aluminium	Grey aluminium	Anthracite grey
	<b>RAL9016</b>			
	Traffic white			
Ingress protection	IP66			
Impact resistance	IK07			

### Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Standard. Optional DALI version available. To be specified at time of ordering.
Surge protection	1/2 kV (optional SP10)
Energy efficiency	C-D (Light source)

### Additional information

Lifetime	Ta=25° L90B10 > 90000h
----------	------------------------

## Options

### Light distribution



[B] symmetric, wide beam



[M] symmetric, medium beam



[EE] symmetric, very narrow beam



[EES] symmetric, very narrow beam, sharp cut-off


### Colour temperature



2700K



3000K







4000K

### Nominal Watt

12 W

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	134-2089	LED-6/12W/2700K	1070 lm	12 W	80
	134-2090	LED-6/12W/3000K	1149.2 lm	12 W	80
	134-2091	LED-6/12W/4000K	1228.5 lm	12 W	80
[B] symmetric, wide beam					
	134-2095	LED-6/12W/2700K	1347.7 lm	12 W	80
	134-2096	LED-6/12W/3000K	1447.6 lm	12 W	80
	134-2097	LED-6/12W/4000K	1547.4 lm	12 W	80
[EE] symmetric, very narrow beam					
	134-2098	LED-6/12W/2700K	1424 lm	12 W	80
	134-2099	LED-6/12W/3000K	1529.5 lm	12 W	80
	134-2100	LED-6/12W/4000K	1635 lm	12 W	80
[EES] symmetric, very narrow beam, sharp cut-off					
	134-2092	LED-6/12W/2700K	1201.1 lm	12 W	80
	134-2093	LED-6/12W/3000K	1290.1 lm	12 W	80
	134-2094	LED-6/12W/4000K	1379 lm	12 W	80
[M] symmetric, medium beam					