

Description

IP66, Class I, IK07. Marine-grade, all aluminium construction. 5CE superior corrosion protection including PCS hardware. Silicone CCG® gasket. Safety glass lens. Two cable entries. Ceiling mount through canopy. Pendulum rod 0.5 - 1.5 m can be selected in 0.1 m increments. To be specified at time of ordering. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. Factory installed LED circuit board. The luminaire is factory-sealed and does not need to be opened during installation.

Other standardised housing lengths available on request.

Optional 2200 K version available. To be specified at time of ordering

Specifications

Material description

Colours	RAL9004	RAL9006	RAL9007	RAL7016
	Signal black	White aluminium	Grey aluminium	Anthracite grey
	RAL9016			
	Traffic white			
Ingress protection	IP66			
Impact resistance	IK07			

Electrical description

Power supply	220-240V / 50-60 Hz
Surge protection	1/2 kV
Energy efficiency	C-D (Light source)

Additional information

Lifetime	Ta=25° L90B10 > 90000h
----------	------------------------

Options**Light distribution**

[B] symmetric, wide beam



[M] symmetric, medium beam



[EE] symmetric, very narrow beam



[EES] symmetric, very narrow beam, sharp cut-off

Colour temperature

2700K



3000K







4000K

Nominal Watt

12 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	134-2394	LED-6/12W/2700K	1070 lm	12 W	80
	134-2395	LED-6/12W/3000K	1149.2 lm	12 W	80
	134-2396	LED-6/12W/4000K	1228.5 lm	12 W	80
[B] symmetric, wide beam					
	134-2440	LED-6/12W/2700K	1347.7 lm	12 W	80
	134-2441	LED-6/12W/3000K	1447.6 lm	12 W	80
	134-2442	LED-6/12W/4000K	1547.4 lm	12 W	80
[EE] symmetric, very narrow beam					
	134-2443	LED-6/12W/2700K	1424 lm	12 W	80
	134-2444	LED-6/12W/3000K	1529.5 lm	12 W	80
	134-2445	LED-6/12W/4000K	1635 lm	12 W	80
[EES] symmetric, very narrow beam, sharp cut-off					
	134-2437	LED-6/12W/2700K	1201.1 lm	12 W	80
	134-2438	LED-6/12W/3000K	1290.1 lm	12 W	80
	134-2439	LED-6/12W/4000K	1379 lm	12 W	80
[M] symmetric, medium beam					