

#### Description

IP66, Class I. IK07. Marine-grade, all aluminium construction. 5CE superior corrosion protection including PCS hardware. Silicone CCG® gasket. Safety glass lens. Two cable entries. Ceiling mount through canopy. Pendulum rod 0.5 - 1.5 m can be selected in 0.1 m increments. To be specified at time at ordering. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. Factory installed LED circuit board. The luminaire is factory-sealed and does not need to be opened during installation.

Other standardised housing lengths available on request.

Optional 2200 K version available. To be specified at time of ordering

## Specifications

### Material description

Colours	<b>RAL9004</b>	<b>RAL9006</b>	<b>RAL9007</b>	<b>RAL7016</b>
	Signal black	White aluminium	Grey aluminium	Anthracite grey
	<b>RAL9016</b>			
	Traffic white			
Ingress protection	IP66			
Impact resistance	IK07			

### Electrical description

Power supply	220-240V / 50-60 Hz
Surge protection	1/2 kV
Energy efficiency	C-D (Light source)

### Additional information

Lifetime	Ta=25° L90B10 > 90000h
----------	------------------------

**Options****Light distribution    Colour temperature    Nominal Watt**

[B]



2700K

12 W




[M]



3000K



[EE]







4000K



[EES]

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	134-2394	LED-6/12W/2700K	1070 lm	12 W	80
	134-2395	LED-6/12W/3000K	1149.2 lm	12 W	80
	134-2396	LED-6/12W/4000K	1228.5 lm	12 W	80
[B]					
	134-2440	LED-6/12W/2700K	1347.7 lm	12 W	80
	134-2441	LED-6/12W/3000K	1447.6 lm	12 W	80
	134-2442	LED-6/12W/4000K	1547.4 lm	12 W	80
[EE]					
	134-2443	LED-6/12W/2700K	1424 lm	12 W	80
	134-2444	LED-6/12W/3000K	1529.5 lm	12 W	80
	134-2445	LED-6/12W/4000K	1635 lm	12 W	80
[EES]					
	134-2437	LED-6/12W/2700K	1201.1 lm	12 W	80
	134-2438	LED-6/12W/3000K	1290.1 lm	12 W	80
	134-2439	LED-6/12W/4000K	1379 lm	12 W	80
[M]					