

### Description

IP66, Class I. IK07. Marine-grade, all aluminium construction. 5CE superior corrosion protection + primer including PCS hardware. Silicone CCG® gasket. Safety glass lens. Two cable entries. Ceiling mount through canopy. Cable suspension 0.5 - 1.5 m. To be specified at time at ordering. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. Factory installed LED circuit board. The luminaire is factory-sealed and does not need to be opened during installation.

Other standardised housing lengths available on request.

Optional 2200 K version available. To be specified at time of ordering.

## Specifications

### Material description

---

Colours	<b>RAL9004</b> Signal black	<b>RAL9006</b> White aluminium	<b>RAL9007</b> Grey aluminium
Ingress protection	IP66		
Impact resistance	IK07		
Corrosion resistance	5CE+Primer		

---

### Electrical description

---

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter in thermally-separated compartment
Surge protection	1/2 kV (optional SP10)
Energy efficiency	C-D (Light source)

---

### Additional information

---

Lifetime	Ta=40° L90B10 > 90000h
----------	------------------------

---

**Options**

**Light distribution    Colour temperature    Nominal Watt**



[B]



3000K

24 W




[M]



2700K



[EE]







4000K



[EES]

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	134-2206	LED-12/24W/2700K	2382.4 lm	24 W	80
	134-2207	LED-12/24W/3000K	2558.9 lm	24 W	80
	134-2208	LED-12/24W/4000K	2735.4 lm	24 W	80
[B]					
	134-2212	LED-12/24W/2700K	2880.3 lm	24 W	80
	134-2213	LED-12/24W/3000K	3093.7 lm	24 W	80
	134-2214	LED-12/24W/4000K	3307 lm	24 W	80
[EE]					
	134-2215	LED-12/24W/2700K	2947.4 lm	24 W	80
	134-2216	LED-12/24W/3000K	3165.7 lm	24 W	80
	134-2217	LED-12/24W/4000K	3384 lm	24 W	80
[EES]					
	134-2209	LED-12/24W/2700K	2875.2 lm	24 W	80
	134-2210	LED-12/24W/3000K	3088.2 lm	24 W	80
	134-2211	LED-12/24W/4000K	3301.2 lm	24 W	80
[M]					