

### Description

IP66, Class I. Class II on request. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® gasket. Safety glass lens. One cable entry, optional T-QPD connector for through wiring available on request. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. Factory installed LED circuit board. The luminaire is factory-sealed and does not need to be opened during installation.

Includes cable connector, for cable 2-12 mm. +/- 10° adjustable to compensate for sloping catenary systems.

Other standardised housing lengths available on request.

Optional 2200 K version available. To be specified at time of ordering.

## Specifications

### Material description

Colours	<b>RAL9004</b> Signal black	<b>RAL9007</b> Grey aluminium	<b>RAL7016</b> Anthracite grey	<b>RAL9016</b> Traffic white
Ingress protection	IP66			
Impact resistance	IK07			

### Electrical description

Power supply	220-240V / 50-60 Hz
Energy efficiency	C-D (Light source)

### Additional information

Lifetime	Ta=25° L90B10 > 90000h
----------	------------------------

**Options****Light distribution    Colour temperature    Nominal Watt**

[B]



2700K

48 W



[M]



3000K



[EE]







4000K



[EES]

**Configurations**

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	134-2276	LED-24/48W/2700K	4916.1 lm	48 W	80
	134-2277	LED-24/48W/3000K	5280.3 lm	48 W	80
	134-2278	LED-24/48W/4000K	5644.5 lm	48 W	80
[B]					
	134-2282	LED-24/48W/2700K	5546.8 lm	48 W	80
	134-2283	LED-24/48W/3000K	5957.7 lm	48 W	80
	134-2284	LED-24/48W/4000K	6368.6 lm	48 W	80
[EE]					
	134-2285	LED-24/48W/2700K	5785.2 lm	48 W	80
	134-2286	LED-24/48W/3000K	6213.7 lm	48 W	80
	134-2287	LED-24/48W/4000K	6642.2 lm	48 W	80
[EES]					
	134-2279	LED-24/48W/2700K	5378.5 lm	48 W	80
	134-2280	LED-24/48W/3000K	5776.9 lm	48 W	80
	134-2281	LED-24/48W/4000K	6175.3 lm	48 W	80
[M]					