

#### Description

IP66, Class I. IK07. Marine-grade, all aluminium construction. 5CE superior corrosion protection + primer including PCS hardware. Silicone CCG® gasket. Safety glass lens. Two cable entries. Ceiling mount through canopy. Cable suspension 0.5 - 1.5 m. To be specified at time at ordering. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. Factory installed LED circuit board. The luminaire is factory-sealed and does not need to be opened during installation.

Other standardised housing lengths available on request.

Optional 2200 K version available. To be specified at time of ordering.

## Specifications

### Material description

---

Colours	<b>RAL9004</b> Signal black	<b>RAL9006</b> White aluminium	<b>RAL9007</b> Grey aluminium
Ingress protection	IP66		
Impact resistance	IK07		
Corrosion resistance	5CE+Primer		

---

### Electrical description

---

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter in thermally-separated compartment
Surge protection	1/2 kV (optional SP10)
Energy efficiency	C-D (Light source)

---

### Additional information

---

Lifetime	Ta=40° L90B10 > 90000h
----------	------------------------

---

**Options**

**Light distribution**



[B] symmetric, wide beam



[M] symmetric, medium beam



[EE] symmetric, very narrow beam



[EES] symmetric, very narrow beam, sharp cut-off

**Colour temperature**



2700K



3000K







4000K

**Nominal Watt**

48 W

**Configurations**

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	134-2306	LED-24/48W/2700K	4242.4 lm	48 W	80
	134-2307	LED-24/48W/3000K	4478.4 lm	48 W	80
	134-2308	LED-24/48W/4000K	4478.4 lm	48 W	80
[B] symmetric, wide beam					
	134-2312	LED-24/48W/2700K	4786.7 lm	48 W	80
	134-2313	LED-24/48W/3000K	5052.9 lm	48 W	80
	134-2314	LED-24/48W/4000K	5052.9 lm	48 W	80
[EE] symmetric, very narrow beam					
	134-2315	LED-24/48W/2700K	4992.4 lm	48 W	80
	134-2316	LED-24/48W/3000K	5270 lm	48 W	80
	134-2317	LED-24/48W/4000K	5270 lm	48 W	80
[EES] symmetric, very narrow beam, sharp cut-off					
	134-2309	LED-24/48W/2700K	4641.5 lm	48 W	80
	134-2310	LED-24/48W/3000K	4899.6 lm	48 W	80
	134-2311	LED-24/48W/4000K	4899.6 lm	48 W	80
[M] symmetric, medium beam					