

Description

IP66, Class I. Class II on request. IK07. Marine-grade, all aluminium construction. 5CE superior corrosion protection including PCS hardware. Silicone CCG® gasket. Safety glass lens. Two cable entries. Ceiling mount through canopy. Cable suspension 0.5 - 1.5 m. To be specified at time at ordering. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. Factory installed LED circuit board. The luminaire is factory-sealed and does not need to be opened during installation.

Other standardised housing lengths available on request.

Optional 2200 K version available. To be specified at time of ordering.

Specifications

Material description

Colours	RAL9004 Signal black	RAL9007 Grey aluminium	RAL7016 Anthracite grey	RAL9016 Traffic white
Ingress protection	IP66			
Impact resistance	IK07			

Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter in thermally-separated compartment
Surge protection	1/2 kV (optional SP10)
Energy efficiency	C-D (Light source)

Additional information

Lifetime	Ta=25° L90B10 > 90000h
----------	------------------------

Options

Light distribution



[B] symmetric, wide beam



[M] symmetric, medium beam



[EE] symmetric, very narrow beam



[EES] symmetric, very narrow beam, sharp cut-off

Colour temperature



2700K



3000K







4000K

Nominal Watt

48 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	134-2306	LED-24/48W/2700K	4242.4 lm	48 W	80
	134-2307	LED-24/48W/3000K	4478.4 lm	48 W	80
	134-2308	LED-24/48W/4000K	4478.4 lm	48 W	80
[B] symmetric, wide beam					
	134-2312	LED-24/48W/2700K	4786.7 lm	48 W	80
	134-2313	LED-24/48W/3000K	5052.9 lm	48 W	80
	134-2314	LED-24/48W/4000K	5052.9 lm	48 W	80
[EE] symmetric, very narrow beam					
	134-2315	LED-24/48W/2700K	4992.4 lm	48 W	80
	134-2316	LED-24/48W/3000K	5270 lm	48 W	80
	134-2317	LED-24/48W/4000K	5270 lm	48 W	80
[EES] symmetric, very narrow beam, sharp cut-off					
	134-2309	LED-24/48W/2700K	4641.5 lm	48 W	80
	134-2310	LED-24/48W/3000K	4899.6 lm	48 W	80
	134-2311	LED-24/48W/4000K	4899.6 lm	48 W	80
[M] symmetric, medium beam					