**Description**

IP66, Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Two cable entries. Ceiling mount through canopy. Cable suspension 1.5 - 5 ft., to be specified at time at ordering. Integral driver in thermally separated compartment. CAD-optimized optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board. 0-10V Dimming comes standard with luminaire. The luminaire is factory-sealed and does not need to be opened during installation.

Optional 2200 K version available, to be specified at time of ordering.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX - 9004 (Black)
+ XXX-XXXX (Accessory 1)

Specifications

Material description

Body	Marine-grade, all aluminium construction			
Colors	RAL9004	RAL9007	RAL9016	RAL8019
	Signal black	Grey aluminium	Traffic white	Grey brown
Ingress protection	IP66			
Impact resistance	IK07			

Electrical description





Power supply	220-240V / 50-60 Hz
Driver / Ballast	Standard. Optional DALI version available. To be specified at time of ordering.
Surge protection	1/2 kV (optional SP10)
Energy efficiency	C-D (Light source)

Additional information




Listings	Contact WE-EF USA for ETL/UL certification status.
Lifetime	Ta=25°/40° L90B10 > 90000h

Options

Light distribution

-  [B] symmetric, wide beam
-  [M] symmetric, medium beam
-  [EE] symmetric, very narrow beam
-  [EES] symmetric, very narrow beam, sharp cut-off





Color temperature

-  2700K
-  3000K
-  4000K

Nominal Watt

48 W

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
	134-2306	LED-24/48W/2700K	4242.4 lm	48 W	80
	134-2307	LED-24/48W/3000K	4478.4 lm	48 W	80
	134-2308	LED-24/48W/4000K	4478.4 lm	48 W	80
[B] symmetric, wide beam					
	134-2312	LED-24/48W/2700K	4786.7 lm	48 W	80
	134-2313	LED-24/48W/3000K	5052.9 lm	48 W	80
	134-2314	LED-24/48W/4000K	5052.9 lm	48 W	80
[EE] symmetric, very narrow beam					
	134-2315	LED-24/48W/2700K	4992.4 lm	48 W	80
	134-2316	LED-24/48W/3000K	5270 lm	48 W	80
	134-2317	LED-24/48W/4000K	5270 lm	48 W	80
[EES] symmetric, very narrow beam, sharp cut-off					
	134-2309	LED-24/48W/2700K	4641.5 lm	48 W	80
	134-2310	LED-24/48W/3000K	4899.6 lm	48 W	80
	134-2311	LED-24/48W/4000K	4899.6 lm	48 W	80
[M] symmetric, medium beam					