



### Description

IP66, Class I. Class II on request. IK07. Marine-grade, all aluminium construction. 5CE superior corrosion protection including PCS hardware. Silicone CCG® gasket. Safety glass lens. Two cable entries. Ceiling mount through canopy. Cable suspension 0.5 - 1.5 m. To be specified at time at ordering. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. Factory installed LED circuit board. The luminaire is factory-sealed and does not need to be opened during installation.

Other standardised housing lengths available on request.

Optional 2200 K version available. To be specified at time of ordering.

## Specifications

### Material description

|                    |                |                 |                |                 |
|--------------------|----------------|-----------------|----------------|-----------------|
| Colours            | <b>RAL9004</b> | <b>RAL9006</b>  | <b>RAL9007</b> | <b>RAL7016</b>  |
|                    | Signal black   | White aluminium | Grey aluminium | Anthracite grey |
|                    | <b>RAL9016</b> |                 |                |                 |
|                    | Traffic white  |                 |                |                 |
| Ingress protection | IP66           |                 |                |                 |
| Impact resistance  | IK07           |                 |                |                 |

### Electrical description

|                   |   |
|-------------------|---|
| Power supply      | 220-240V / 50-60 Hz   |
| Driver / Ballast  | Standard. Optional DALI version available. To be specified at time of ordering. |
| Surge protection  | 1/2 kV (optional SP10)  |
| Energy efficiency | C-D (Light source)  |

### Additional information

|          |                        |
|----------|------------------------|
| Lifetime | Ta=25° L90B10 > 90000h |
|----------|------------------------|

## Options

Light distribution   Colour temperature   Nominal Watt

---

## Configurations

| Light distribution | Part ID | Light source | Rated lumens | Rated input power | CRI |
|--------------------|---------|--------------|--------------|-------------------|-----|
|--------------------|---------|--------------|--------------|-------------------|-----|