



Description

IP66, Class I. IK07. Marine-grade, all aluminium construction. 5CE superior corrosion protection + primer including PCS hardware. Silicone CCG® gasket. Safety glass lens. Two cable entries. Ceiling mount through canopy. Cable suspension 0.5 - 1.5 m. To be specified at time at ordering. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. Factory installed LED circuit board. Tunable White Technology. The luminaire is factory-sealed and does not need to be opened during installation.

Other standardised housing lengths available on request.

Specifications

Material description

| | | | |
|----------------------|--------------------------------|-----------------------------------|----------------------------------|
| Colours | RAL9004 Signal black | RAL9006 White aluminium | RAL9007 Grey aluminium |
| Ingress protection | IP66 | | |
| Impact resistance | IK07 | | |
| Corrosion resistance | 5CE+Primer | | |

Electrical description

| | |
|-------------------|--------------------|
| Energy efficiency | C-D (Light source) |
|-------------------|--------------------|

Additional information

Options

Light distribution Colour temperature Nominal Watt

Configurations

| Light distribution | Part ID | Light source | Rated lumens | Rated input power | CRI |
|--------------------|---------|--------------|--------------|-------------------|-----|
|--------------------|---------|--------------|--------------|-------------------|-----|
