

**Description**

IP66, Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Two cable entries. Ceiling mount through canopy. Cable suspension 1.5 - 5 ft., to be specified at time at ordering. Integral driver in thermally separated compartment. CAD-optimized optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board. Tunable White technology. DALI interface. The luminaire is factory-sealed and does not need to be opened during installation.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX - 9004 (Black)  
+ XXX-XXXX (Accessory 1)

**Specifications**

**Material description**

Body	Marine-grade, all aluminium construction			
Colors	<b>RAL9004</b>	<b>RAL9007</b>	<b>RAL9016</b>	<b>RAL8019</b>
	Signal black	Grey aluminium	Traffic white	Grey brown
Ingress protection	IP66			
Impact resistance	IK07			

**Electrical description**

Energy efficiency	C-D (Light source)
-------------------	--------------------

**Additional information**

Height x Diameter (inches)	11.8 x 7.7
Listings	Contact WE-EF USA for ETL/UL certification status.

**Options**

Light distribution   Color temperature   Nominal Watt

### Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
--------------------	---------	--------------	------------------	-------------------	-----