

### Description

IP66, Class I, IK07. Marine-grade, all aluminium construction. 5CE superior corrosion protection including PCS hardware. Silicone CCG® gasket. Safety glass lens. Two cable entries. Ceiling mount through canopy. Pendulum rod 0.5 - 1.5 m can be selected in 0.1 m increments. To be specified at time at ordering. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. Factory installed LED circuit board. The luminaire is factory-sealed and does not need to be opened during installation.

Other standardised housing lengths available on request.

Optional 2200 K version available. To be specified at time of ordering.

## Specifications

### Material description

Colours	<b>RAL9004</b>	<b>RAL9006</b>	<b>RAL9007</b>	<b>RAL7016</b>
	Signal black	White aluminium	Grey aluminium	Anthracite grey
	<b>RAL9016</b>			
	Traffic white			
Ingress protection	IP66			
Impact resistance	IK07			

### Electrical description

Power supply	220-240V / 50-60 Hz
Surge protection	1/2 kV (optional SP10)
Energy efficiency	C-D (Light source)

### Additional information

Lifetime	Ta=25° L90B10 > 90000h
----------	------------------------

**Options****Light distribution    Colour temperature    Nominal Watt**

[B]



2700K

48 W




[M]



3000K



[EE]







4000K



[EES]

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	134-2520	LED-24/48W/2700K	4916.1 lm	48 W	80
	134-2521	LED-24/48W/3000K	5280.3 lm	48 W	80
	134-2522	LED-24/48W/4000K	5644.5 lm	48 W	80
[B]					
	134-2526	LED-24/48W/2700K	5546.8 lm	48 W	80
	134-2527	LED-24/48W/3000K	5957.7 lm	48 W	80
	134-2528	LED-24/48W/4000K	6368.6 lm	48 W	80
[EE]					
	134-2529	LED-24/48W/2700K	5785.2 lm	48 W	80
	134-2530	LED-24/48W/3000K	6213.7 lm	48 W	80
	134-2531	LED-24/48W/4000K	6642.2 lm	48 W	80
[EES]					
	134-2523	LED-24/48W/2700K	5378.5 lm	48 W	80
	134-2524	LED-24/48W/3000K	5776.9 lm	48 W	80
	134-2525	LED-24/48W/4000K	6175.3 lm	48 W	80
[M]					