

Description

IP55, Class I. Class II on request. IK10. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone rubber gasket. Polycarbonate main lens. Two cable entries. Factory installed LED circuit board. Integral EC electronic converter.

Specifications

Material description

| | | | | |
|----------------------|---|-----------------------------------|---------------------------------|-----------------------------------|
| Body | Marine-grade die-cast aluminium alloy | | | |
| Lens | Polycarbonate main lens | | | |
| Colours | RAL9004 Signal black | RAL9006 White aluminium | RAL9016 Traffic white | RAL7016 Anthracite grey |
| | RAL9007 Grey aluminium | | | |
| Gasket | Silicone rubber gasket | | | |
| Fasteners | PCS Polymer Coated Stainless Steel Hardware | | | |
| Ingress protection | IP55 | | | |
| Impact resistance | IK10 | | | |
| Corrosion resistance | 5CE | | | |

Electrical description

| | |
|-------------------|----------------------------------|
| Power supply | 220-240V / 50-60 Hz |
| Driver / Ballast | Integral EC electronic converter |
| Surge protection | 1/2 kV |
| Energy efficiency | D-E (Light source) |

Additional information

| | |
|----------|------------------------|
| Lifetime | Ta=25° L70B50 > 50000h |
|----------|------------------------|

Options


Light distribution Colour temperature Nominal Watt

[]



3000K

28 W



4000K



2700K

Configurations

| Light distribution | Part ID | Light source | Rated lumens | Rated input power | CRI |
|--------------------|----------|-----------------|--------------|-------------------|-----|
| [] | 195-0898 | LED-1/28W/2700K | 4570.5 lm | 28 W | 80 |
| | 195-9542 | LED-1/28W/3000K | 4760.5 lm | 28 W | 80 |
| | 195-9543 | LED-1/28W/4000K | 4970.5 lm | 28 W | 80 |