

#### Description

IP66, Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Silicone CCG\_R\_ gasket. Safety glass lens. Two cable entries. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. OLC\_R\_ One LED Concept. Factory installed LED circuit board. The luminaire is factory-sealed and does not need to be opened during the installation.

A pre-installation blackout, proud or flush, is available and recommended for mounting in concrete ceilings. To be ordered separately.

2700 K option available on request. Optional 2200 K version available. To be specified at time of ordering.

## Specifications

### Material description

---

Body	Marine-grade, die-cast aluminium alloy						
Lens	Safety glass lens						
Colours	<table><tr><td><b>RAL9004</b></td><td><b>RAL9006</b></td><td><b>RAL9007</b></td></tr><tr><td>Signal black</td><td>White aluminium</td><td>Grey aluminium</td></tr></table>	<b>RAL9004</b>	<b>RAL9006</b>	<b>RAL9007</b>	Signal black	White aluminium	Grey aluminium
<b>RAL9004</b>	<b>RAL9006</b>	<b>RAL9007</b>					
Signal black	White aluminium	Grey aluminium					
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)						
Ingress protection	IP66						
Impact resistance	IK07						
Corrosion resistance	5CE+Primer						

---

### Electrical description

---

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter in thermally-separated compartment
Surge protection	1/2 kV
Energy efficiency	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on <a href="http://www.we-ef.com">www.we-ef.com</a> for further details.

---

### Additional information

---

Lifetime	Ta=40° L90B10 > 90000h
----------	------------------------

---

## Options

### Light distribution



[B] symmetric, wide beam



[M] symmetric, medium beam



[EE] symmetric, very narrow beam




[EES] symmetric, very narrow beam, sharp cut-off

### Colour temperature



3000K



4000K







2700K

### Nominal Watt

12 W

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	134-1907	LED-6/12W/2700K	1254.2 lm	12 W	80
	134-1625	LED-6/12W/3000K	1347.1 lm	12 W	80
	134-1626	LED-6/12W/4000K	1440 lm	12 W	80
[B] symmetric, wide beam					
	134-1909	LED-6/12W/2700K	1393.3 lm	12 W	80
	134-1631	LED-6/12W/3000K	1496.5 lm	12 W	80
	134-1632	LED-6/12W/4000K	1599.7 lm	12 W	80
[EE] symmetric, very narrow beam					
	134-1910	LED-6/12W/2700K	1499.6 lm	12 W	80
	134-1633	LED-6/12W/3000K	1610.7 lm	12 W	80
	134-1634	LED-6/12W/4000K	1721.8 lm	12 W	80
[EES] symmetric, very narrow beam, sharp cut-off					
	134-1908	LED-6/12W/2700K	1407.5 lm	12 W	80
	134-1627	LED-6/12W/3000K	1511.8 lm	12 W	80
	134-1628	LED-6/12W/4000K	1616.1 lm	12 W	80
[M] symmetric, medium beam					