

Description

IP66, Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Silicone CCG_R_ gasket. Safety glass lens. Two cable entries. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. OLC_R_ One LED Concept. Factory installed LED circuit board. The luminaire is factory- sealed and does not need to be opened during the installation.

A pre-installation blackout, proud or flush, is available and recommended for mounting in concrete ceilings. To be ordered separately.

2700 K option available on request. Optional 2200 K version available. To be specified at time of ordering.

Specifications

Material description

Body	Marine-grade, die-cast aluminium alloy						
Lens	Safety glass lens						
Colours	<table><tr><td>RAL9004</td><td>RAL9006</td><td>RAL9007</td></tr><tr><td>Signal black</td><td>White aluminium</td><td>Grey aluminium</td></tr></table>	RAL9004	RAL9006	RAL9007	Signal black	White aluminium	Grey aluminium
RAL9004	RAL9006	RAL9007					
Signal black	White aluminium	Grey aluminium					
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)						
Ingress protection	IP66						
Impact resistance	IK07						
Corrosion resistance	5CE+Primer						

Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter in thermally-separated compartment
Surge protection	1/2 kV
Energy efficiency	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details.

Additional information

Lifetime	Ta=40° L90B10 > 90000h
----------	------------------------

Options**Light distribution Colour temperature Nominal Watt**

[B]




3000K

12 W



[M]



4000K



[EE]







2700K



[EES]

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	134-1907	LED-6/12W/2700K	1254.2 lm	12 W	80
	134-1625	LED-6/12W/3000K	1347.1 lm	12 W	80
	134-1626	LED-6/12W/4000K	1440 lm	12 W	80
[B]	<hr/>				
	134-1909	LED-6/12W/2700K	1393.3 lm	12 W	80
	134-1631	LED-6/12W/3000K	1496.5 lm	12 W	80
	134-1631	LED-6/12W/3000K	1496.5 lm	12 W	80
	134-1632	LED-6/12W/4000K	1599.7 lm	12 W	80
[EE]	<hr/>				
	134-1910	LED-6/12W/2700K	1499.6 lm	12 W	80
	134-1633	LED-6/12W/3000K	1610.7 lm	12 W	80
	134-1633	LED-6/12W/3000K	1610.7 lm	12 W	80
	134-1634	LED-6/12W/4000K	1721.8 lm	12 W	80
[EES]	<hr/>				
	134-1908	LED-6/12W/2700K	1407.5 lm	12 W	80
	134-1908	LED-6/12W/2700K	1407.5 lm	12 W	80
	134-1627	LED-6/12W/3000K	1511.8 lm	12 W	80
	134-1627	LED-6/12W/3000K	1511.8 lm	12 W	80
	134-1628	LED-6/12W/4000K	1616.1 lm	12 W	80
	134-1628	LED-6/12W/4000K	1616.1 lm	12 W	80
[M]	<hr/>				