

Description

DOC110 LED for remodel projects. For new construction, see DOC110 LED [New Construction] version.

IP66, Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Separate IP66 driver housing. CAD-optimized optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board. 0-10V Dimming comes standard with luminaire.

A pre-installation blockout, proud or flush, is available and recommended for mounting in concrete ceilings; to be ordered separately.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX - 9004 (Black)
+ XXX-XXXX (Accessory 1)

Specifications

Material description

Body	Marine-grade, die-cast aluminium alloy			
Lens	Safety glass lens			
Colors	RAL9004	RAL9016	RAL8019	RAL9007
	Signal black	Traffic white	Grey brown	Grey aluminium
Fasteners	PCS Polymer Coated Stainless Steel Hardware			
Ingress protection	IP66			
Impact resistance	IK07			
Corrosion resistance	5CE			








Electrical description

Power supply	Integral 120-277V/0-10V dimming driver
Driver / Ballast	Integral EC electronic converter in thermally-separated compartment
Surge protection	1/2 kV
Energy efficiency	C-D (Light source)





Additional information

Diameter (inches)	4.60
Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.
Lifetime	Ta=25°/40° L90B10 > 90000h

Options

Light distribution	Color temperature	Nominal Watt
 [B]	 3000K	12 W
 [M]	 4000K	
 [EE]	 2700K	
 [EES]		

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
	134-1907	LED-6/12W/2700K	1254.2 lm	12 W	80
	134-1625	LED-6/12W/3000K	1347.1 lm	12 W	80
	134-1626	LED-6/12W/4000K	1440 lm	12 W	80
[B]					
	134-1909	LED-6/12W/2700K	1393.3 lm	12 W	80
	134-1631	LED-6/12W/3000K	1496.5 lm	12 W	80
	134-1631	LED-6/12W/3000K	1496.5 lm	12 W	80
[EE]	134-1632	LED-6/12W/4000K	1599.7 lm	12 W	80
	134-1632	LED-6/12W/4000K	1599.7 lm	12 W	80
	134-1910	LED-6/12W/2700K	1499.6 lm	12 W	80
	134-1633	LED-6/12W/3000K	1610.7 lm	12 W	80
	134-1633	LED-6/12W/3000K	1610.7 lm	12 W	80
	134-1634	LED-6/12W/4000K	1721.8 lm	12 W	80
[EES]	134-1634	LED-6/12W/4000K	1721.8 lm	12 W	80
	134-1908	LED-6/12W/2700K	1407.5 lm	12 W	80
	134-1908	LED-6/12W/2700K	1407.5 lm	12 W	80
	134-1627	LED-6/12W/3000K	1511.8 lm	12 W	80
	134-1627	LED-6/12W/3000K	1511.8 lm	12 W	80
	134-1628	LED-6/12W/4000K	1616.1 lm	12 W	80
	134-1628	LED-6/12W/4000K	1616.1 lm	12 W	80
[M]					