

Description

DOC120-FT LED for new construction. For remodel projects, see DOC120-FT LED [For Remodel] version.

IP66, Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Integral driver in thermally separated compartment. Darklight anodized aluminum reflector for superior illumination and glare control. Factory-installed LED circuit board. DMX interface. The luminaire is factory-sealed and does not need to be opened during the installation.

A pre-installation blockout, proud or flush, is available and recommended for mounting in concrete ceilings; to be ordered separately.


A maximum of one internal optical accessory, to be specified at time of ordering.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX - 9004 (Black)
+ XXX-XXXX (Accessory 1)

Specifications






Material description

Colors	 RAL9004 Signal black	 RAL9007 Grey aluminium	 RAL9016 Traffic white	 RAL8019 Grey brown
Ingress protection	IP66			
Impact resistance	IK07			




Electrical description

Additional information

Options

Light distribution	Color temperature	Nominal Watt
 [W] bi-symmetric, wide beam	 3000K	17 W 24 W
 [M] symmetric, medium beam	 4000K	
 [N] bi-symmetric, narrow beam		

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 [M] symmetric, medium beam	134-6252_us	LED-1/17W/3000K	1654.2 lm	17 W	80
	134-6258_us	LED-1/17W/4000K	1722.9 lm	17 W	80
	134-6258_us	LED-12/24W/3000K	2542.8 lm	24 W	80
	134-6259_us	LED-12/24W/4000K	2542.8 lm	24 W	80
 [N] bi-symmetric, narrow beam	134-6254_us	LED-1/17W/3000K	775.8 lm	17 W	80
	134-6255_us	LED-1/17W/4000K	808 lm	17 W	80
	134-6260_us	LED-1/24W/3000K	1055 lm	24 W	80
	134-6261_us	LED-1/24W/4000K	1100.6 lm	24 W	80
 [W] bi-symmetric, wide beam	134-6250_us	LED-1/17W/3000K	1641.1 lm	17 W	80
	134-6251_us	LED-1/17W/4000K	1709.2 lm	17 W	80
	134-6256_us	LED-1/24W/3000K	2231.7 lm	24 W	80
	134-6257_us	LED-1/24W/4000K	2328.2 lm	24 W	80