

Description

IP66, Class I. Class II on request. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Two cable entries. Integral EC electronic converter in thermally separated compartment. Darklight anodised aluminium reflector for superior illumination and glare control. Factory-installed LED circuit board.

Suitable for mounting up to max. 40 mm ceiling thickness. A pre-installation blockout, proud or flush, is available and recommended for mounting in concrete ceilings. To be ordered separately.

A maximum of one internal optical accessory.

The luminaire is not suitable for chlorine containing environments e.g. swimming pool. Special version suitable for chlorine containing environments, on request. Must be specified at time of ordering.

Specifications

Material description

Colours	RAL9004	RAL9006	RAL9007	RAL7016
	Signal black	White aluminium	Grey aluminium	Anthracite grey
	RAL9016			
	Traffic white			
Ingress protection	IP66			
Impact resistance	IK07			

Electrical description

Energy efficiency	D (Light source)
-------------------	------------------

Additional information

Lifetime	Ta=25° L70B50 > 50000h
----------	------------------------

Options**Light distribution**

[B] symmetric, wide beam




[M] symmetric, medium beam



[E] symmetric, narrow beam

Colour temperature

3000K



4000K






2700K

Nominal Watt

17 W

24 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [B] symmetric, wide beam	134-1919	LED-1/17W/2700K	1666.6 lm	17 W	80
	134-1855	LED-1/17W/3000K	1743.3 lm	17 W	80
	134-1856	LED-1/17W/4000K	1817.1 lm	17 W	80
	134-1920	LED-1/24W/2700K	2299.8 lm	24 W	80
	134-1861	LED-1/24W/3000K	2396.3 lm	24 W	80
	134-1862	LED-1/24W/4000K	2498.6 lm	24 W	80
 [E] symmetric, narrow beam	134-1923	LED-1/17W/2700K	787.9 lm	17 W	80
	134-1859	LED-1/17W/3000K	824.1 lm	17 W	80
	134-1860	LED-1/17W/4000K	859 lm	17 W	80
	134-1924	LED-1/24W/2700K	1087.2 lm	24 W	80
	134-1865	LED-1/24W/3000K	1132.9 lm	24 W	80
	134-1866	LED-1/24W/4000K	1181.2 lm	24 W	80
 [M] symmetric, medium beam	134-1921	LED-1/17W/2700K	1680 lm	17 W	80
	134-1857	LED-1/17W/3000K	1757.2 lm	17 W	80
	134-1858	LED-1/17W/4000K	1831.6 lm	17 W	80
	134-1922	LED-1/24W/2700K	2318.2 lm	24 W	80
	134-1863	LED-1/24W/3000K	2415.5 lm	24 W	80
	134-1864	LED-1/24W/4000K	2518.5 lm	24 W	80