

Description

IP66, Class I. Class II on request. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Two cable entries. Integral EC electronic converter in thermally separated compartment. Darklight anodised aluminium reflector for superior illumination and glare control. Factory-installed LED circuit board.

Suitable for mounting up to max. 40 mm ceiling thickness. A pre-installation blockout, proud or flush, is available and recommended for mounting in concrete ceilings. To be ordered separately.

A maximum of one internal optical accessory.

The luminaire is not suitable for chlorine containing environments e.g. swimming pool. Special version suitable for chlorine containing environments, on request. Must be specified at time of ordering.

Specifications

Material description

| | | | | |
|--------------------|----------------|-----------------|----------------|-----------------|
| Colours | RAL9004 | RAL9006 | RAL9007 | RAL7016 |
| | Signal black | White aluminium | Grey aluminium | Anthracite grey |
| | RAL9016 | | | |
| | Traffic white | | | |
| Ingress protection | IP66 | | | |
| Impact resistance | IK07 | | | |

Electrical description

| | |
|-------------------|------------------|
| Energy efficiency | D (Light source) |
|-------------------|------------------|

Additional information

| | |
|----------|------------------------|
| Lifetime | Ta=25° L70B50 > 50000h |
|----------|------------------------|

Options**Light distribution Colour temperature Nominal Watt**

[B]




3000K

17 W

24 W



[M]



4000K






[E]



2700K

Configurations

| Light distribution | Part ID | Light source | Rated lumens | Rated input power | CRI |
|---|----------|-----------------|--------------|-------------------|-----|
|  [B] | 134-1919 | LED-1/17W/2700K | 1666.6 lm | 17 W | 80 |
| | 134-1855 | LED-1/17W/3000K | 1743.3 lm | 17 W | 80 |
| | 134-1856 | LED-1/17W/4000K | 1817.1 lm | 17 W | 80 |
| | 134-1920 | LED-1/24W/2700K | 2299.8 lm | 24 W | 80 |
| | 134-1861 | LED-1/24W/3000K | 2396.3 lm | 24 W | 80 |
| | 134-1862 | LED-1/24W/4000K | 2498.6 lm | 24 W | 80 |
|  [E] | 134-1923 | LED-1/17W/2700K | 787.9 lm | 17 W | 80 |
| | 134-1859 | LED-1/17W/3000K | 824.1 lm | 17 W | 80 |
| | 134-1860 | LED-1/17W/4000K | 859 lm | 17 W | 80 |
| | 134-1924 | LED-1/24W/2700K | 1087.2 lm | 24 W | 80 |
| | 134-1865 | LED-1/24W/3000K | 1132.9 lm | 24 W | 80 |
| | 134-1866 | LED-1/24W/4000K | 1181.2 lm | 24 W | 80 |
|  [M] | 134-1921 | LED-1/17W/2700K | 1680 lm | 17 W | 80 |
| | 134-1857 | LED-1/17W/3000K | 1757.2 lm | 17 W | 80 |
| | 134-1858 | LED-1/17W/4000K | 1831.6 lm | 17 W | 80 |
| | 134-1922 | LED-1/24W/2700K | 2318.2 lm | 24 W | 80 |
| | 134-1863 | LED-1/24W/3000K | 2415.5 lm | 24 W | 80 |
| | 134-1864 | LED-1/24W/4000K | 2518.5 lm | 24 W | 80 |