

#### Description

IP66, Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Silicone CCG\_R\_ Controlled Compression Gasket. Safety glass lens. Two cable entries. Integral EC electronic converter in thermally separated compartment. Darklight anodised aluminium reflector for superior illumination and glare control. Factory-installed LED circuit board. DALI Interface.

A pre-installation blackout, proud or flush, is available and recommended for mounting in concrete ceilings. To be ordered separately.

A maximum of one internal optical accessory.

## Specifications

### Material description

---

Colours	<b>RAL9004</b> Signal black	<b>RAL9006</b> White aluminium	<b>RAL9007</b> Grey aluminium
Ingress protection	IP66		
Impact resistance	IK07		
Corrosion resistance	5CE+Primer		

---

### Electrical description

---

Driver / Ballast	Integral EC electronic converter in thermally-separated compartment
Energy efficiency	D (Light source)

---







### Additional information

---




Lifetime	Ta=40° L70B50 > 50000h
----------	------------------------

---

**Options**

Light distribution	Colour temperature	Nominal Watt
 [B]	 3000K	17 W
		24 W
 [M]	 4000K	
 [E]	 2700K	

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [B]	134-1919	LED-1/17W/2700K	1666.6 lm	17 W	80
	134-1855	LED-1/17W/3000K	1743.3 lm	17 W	80
	134-1856	LED-1/17W/4000K	1817.1 lm	17 W	80
	134-1920	LED-1/24W/2700K	2299.8 lm	24 W	80
	134-1861	LED-1/24W/3000K	2396.3 lm	24 W	80
	134-1862	LED-1/24W/4000K	2498.6 lm	24 W	80
 [E]	134-1923	LED-1/17W/2700K	787.9 lm	17 W	80
	134-1859	LED-1/17W/3000K	824.1 lm	17 W	80
	134-1860	LED-1/17W/4000K	859 lm	17 W	80
	134-1924	LED-1/24W/2700K	1087.2 lm	24 W	80
	134-1865	LED-1/24W/3000K	1132.9 lm	24 W	80
	134-1866	LED-1/24W/4000K	1181.2 lm	24 W	80
 [M]	134-1921	LED-1/17W/2700K	1680 lm	17 W	80
	134-1857	LED-1/17W/3000K	1757.2 lm	17 W	80
	134-1858	LED-1/17W/4000K	1831.6 lm	17 W	80
	134-1922	LED-1/24W/2700K	2318.2 lm	24 W	80
	134-1863	LED-1/24W/3000K	2415.5 lm	24 W	80
	134-1864	LED-1/24W/4000K	2518.5 lm	24 W	80