

Description

IP66, Class I, IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Silicone CCG_R_ Controlled Compression Gasket. Safety glass lens. Two cable entries. Integral EC electronic converter in thermally separated compartment. Darklight anodised aluminium reflector for superior illumination and glare control. Factory-installed LED circuit board. Tunable White Technology. DALI Interface.

The luminaire is factory- sealed and does not need to be opened during the installation. A pre-installation blackout, proud or flush, is available and recommended for mounting in concrete ceilings. To be ordered separately.

A maximum of one internal optical accessory.

Specifications

Material description

Colours	RAL9004 Signal black	RAL9006 White aluminium	RAL9007 Grey aluminium
Ingress protection	IP66		
Impact resistance	IK07		
Corrosion resistance	5CE+Primer		

Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter in thermally-separated compartment
Energy efficiency	E (Light source)

Additional information

Lifetime	Ta=40° L70B50 > 50000h
----------	------------------------

Options**Light distribution****Colour temperature****Nominal Watt**

[B] symmetric, wide beam

2700-6000K

17 W






[M] symmetric, medium beam



[E] symmetric, narrow beam

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 <p>[B] symmetric, wide beam</p>	134-1868	LED-2/17W/2700-6000K	1091.8 lm	17 W	80
 <p>[E] symmetric, narrow beam</p>	134-1874	LED-2/17W/2700-6000K	481.8 lm	17 W	80
 <p>[M] symmetric, medium beam</p>	134-1871	LED-2/17W/2700-6000K	1107.7 lm	17 W	80