

Description

IP66, Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG_R_ Controlled Compression Gasket. Safety glass lens. Two cable entries. Integral EC electronic converter in thermally separated compartment. Darklight anodised aluminium reflector for superior illumination and glare control. Factory-installed LED circuit board. Tunable White Technology. DMX Interface.

The luminaire is factory- sealed and does not need to be opened during the installation. A pre-installation blockout, proud or flush, is available and recommended for mounting in concrete ceilings. To be ordered separately.

A maximum of one internal optical accessory.

Specifications

Material description

Colors	RAL9004 Signal black	RAL9007 Grey aluminium	RAL9016 Traffic white	RAL8019 Grey brown
Ingress protection	IP66			
Impact resistance	IK07			




Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	DMX
Energy efficiency	E (Light source)




Additional information

Listings	ETL listed. Suitable for wet locations. IC rated (for insulated ceilings).
Lifetime	Ta=25°/40° L70B50 > 40000h

Options

Light distribution	Color temperature	Nominal Watt
 [W] bi-symmetric, wide beam	2700-6000K	17 W
 [M] symmetric, medium beam		
 [N] bi-symmetric, narrow beam		

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 <p>[M] symmetric, medium beam</p>	134-1871_us	LED-2/17W/2700-6000K	1107.7 lm	17 W	80
 <p>[N] bi-symmetric, narrow beam</p>	134-1874_us	LED-2/17W/2700-6000K	481.8 lm	17 W	80
 <p>[W] bi-symmetric, wide beam</p>	134-1868_us	LED-2/17W/2700-6000K	1091.8 lm	17 W	80