

### Description

IP66, Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG\_R\_ Controlled Compression Gasket. Safety glass lens. Two cable entries. Integral EC electronic converter in thermally separated compartment. Darklight anodised aluminium reflector for superior illumination and glare control. Factory-installed LED circuit board. Tunable White Technology. DMX Interface.

The luminaire is factory- sealed and does not need to be opened during the installation. A pre-installation blockout, proud or flush, is available and recommended for mounting in concrete ceilings. To be ordered separately.

A maximum of one internal optical accessory.

## Specifications

### Material description

Colors	<b>RAL9004</b> Signal black	<b>RAL9007</b> Grey aluminium	<b>RAL9016</b> Traffic white	<b>RAL8019</b> Grey brown
Ingress protection	IP66			
Impact resistance	IK07			

### Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	DMX
Energy efficiency	E (Light source)

### Additional information

Diameter (inches)	6.10
Listings	ETL listed. Suitable for wet locations. IC rated (for insulated ceilings).
Lifetime	Ta=25°/40° L70B50 > 40000h

**Options**

**Light distribution**    **Color temperature**    **Nominal Watt**



[B]

2700-6000K

17 W






[M]



[E]

**Configurations**

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 <p>[B]</p>	134-1868	LED-2/17W/2700-6000K	1091.8 lm	17 W	80
 <p>[E]</p>	134-1874	LED-2/17W/2700-6000K	481.8 lm	17 W	80
 <p>[M]</p>	134-1871	LED-2/17W/2700-6000K	1107.7 lm	17 W	80