

### Description

DOC120 LED for remodel projects. For new construction, see DOC120 LED [New Construction] version.

IP66, Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Separate IP66 driver housing. CAD-optimized optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board. 0-10V Dimming comes standard with luminaire.

A pre-installation blockout, proud or flush, is available and recommended for mounting in concrete ceilings; to be ordered separately.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX - 9004 (Black)  
+ XXX-XXXX (Accessory 1)

## Specifications

### Material description

Body	Marine-grade, die-cast aluminium alloy			
Colors	<b>RAL9004</b> Signal black	<b>RAL9016</b> Traffic white	<b>RAL8019</b> Grey brown	<b>RAL9007</b> Grey aluminium
Fasteners	PCS Polymer Coated Stainless Steel Hardware			
Ingress protection	IP66			
Impact resistance	IK07			

### Electrical description








Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Integral EC electronic converter in thermally-separated compartment
Surge protection	6/6 kV
Energy efficiency	C-D (Light source)

### Additional information




Listings	Contact WE-EF USA for ETL/UL certification status.
Lifetime	Ta=25°/40° L90B10 > 90000h

**Options**

**Light distribution**

- 
[W] bi-symmetric, wide beam
- 
[M] symmetric, medium beam
- 
[VN] symmetric, very narrow beam
- 
[VNS] symmetric, very narrow beam, sharp cut-off
- 
[B] symmetric, wide beam
- 
[EE] symmetric, very narrow beam
- 
[EES] symmetric, very narrow beam, sharp cut-off







**Color temperature**

- 
3000K
- 
4000K
- 
2700K


**Nominal Watt**

24 W

## Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 <p>[B] symmetric, wide beam</p>	134-1911	LED-12/24W/2700K	2522.3 lm	24 W	80
 <p>[EE] symmetric, very narrow beam</p>	134-1913	LED-12/24W/2700K	2684.8 lm	24 W	80
 <p>[EES] symmetric, very narrow beam, sharp cut-off</p>	134-1914	LED-12/24W/2700K	2865.6 lm	24 W	80
 <p>[M] symmetric, medium beam</p>	134-1912	LED-12/24W/2700K	2791.8 lm	24 W	80
	134-1739_us	LED-12/24W/3000K	2998.6 lm	24 W	80
	134-1740_us	LED-12/24W/4000K	3205.4 lm	24 W	80
 <p>[M] symmetric, medium beam</p>	134-1741_us	LED-12/24W/3000K	2883.7 lm	24 W	80
	134-1742_us	LED-12/24W/4000K	3082.5 lm	24 W	80
 <p>[VN] symmetric, very narrow beam</p>	134-1743_us	LED-12/24W/3000K	3077.9 lm	24 W	80
	134-1744_us	LED-12/24W/4000K	3290.2 lm	24 W	80
<p>[VNS] symmetric, very narrow beam, sharp cut-off</p>	134-1737_us	LED-12/24W/3000K	2709.2 lm	24 W	80

---

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 <p data-bbox="81 525 357 558">[W] bi-symmetric, wide beam</p>	134-1738_us	LED-12/24W/4000K	2896 lm	24 W	80

---