**Description**

DOC140-FT LED for new construction. For remodel projects, see DOC140-FT LED [For Remodel] version.

IP66, Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Two cable entries. Integral driver in thermally separated compartment. CAD-optimized optics for superior illumination and glare control. Factory installed LED circuit board. DMX interface. The luminaire is factory-sealed and does not need to be opened during the installation.

A pre-installation blockout, proud or flush, is available and recommended for mounting in concrete ceilings; to be ordered separately.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX - 9004 (Black)
+ XXX-XXXX (Accessory 1)

Specifications






Material description

Colors	RAL9004 Signal black	RAL9007 Grey aluminium	RAL9016 Traffic white	RAL8019 Grey brown
Ingress protection	IP66			
Impact resistance	IK07			




Electrical description

Additional information

Options

Light distribution	Color temperature	Nominal Watt
 [W] bi-symmetric, wide beam	 3000K	24 W 37 W
 [M] symmetric, medium beam	 4000K	
 [N] bi-symmetric, narrow beam		

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 [M] symmetric, medium beam	134-6452_us	LED-1/24W/3000K	2193.9 lm	24 W	80
	134-6453_us	LED-1/24W/4000K	2290.7 lm	24 W	80
	134-6458_us	LED-1/37W/3000K	3167.1 lm	37 W	80
	134-6459_us	LED-1/37W/4000K	3301.6 lm	37 W	80
 [N] bi-symmetric, narrow beam	134-6454_us	LED-1/24W/3000K	1212.9 lm	24 W	
	134-6455_us	LED-1/24W/4000K	1266.4 lm	24 W	80
	134-6460_us	LED-1/37W/3000K	1751 lm	37 W	80
	134-6461_us	LED-1/37W/4000K	1825.3 lm	37 W	80
 [W] bi-symmetric, wide beam	134-6450_us	LED-1/24W/3000K	2154.9 lm	24 W	80
	134-6451_us	LED-1/24W/4000K	2250 lm	24 W	80
	134-6456_us	LED-1/37W/3000K	3110.9 lm	37 W	80
	134-6457_us	LED-1/37W/4000K	3242.9 lm	37 W	80