

Description

IP66, Class I, IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Two cable entries.

Integral EC electronic converter in thermally separated compartment. Darklight anodised aluminium reflector for superior illumination and glare control. Factory-installed LED circuit board. Tunable White Technology. DALI Interface. The luminaire is factory-sealed and does not need to be opened during the installation.

Pre-installation blockout, proud or flush, is available and recommended for mounting in concrete ceilings. To be ordered separately.

A maximum of one internal optical accessory.

Specifications

Material description

| | | | | |
|--------------------|--------------------------------|----------------------------------|-----------------------------------|---------------------------------|
| Colours | RAL9004 Signal black | RAL9007 Grey aluminium | RAL7016 Anthracite grey | RAL9016 Traffic white |
| Ingress protection | IP66 | | | |
| Impact resistance | IK07 | | | |

Electrical description

| | |
|-------------------|---|
| Power supply | 220-240V / 50-60 Hz |
| Driver / Ballast | Integral EC electronic converter in thermally-separated compartment |
| Energy efficiency | E (Light source) |

Additional information

| | |
|----------|------------------------|
| Lifetime | Ta=25° L70B50 > 50000h |
|----------|------------------------|

Options**Light distribution****Colour temperature****Nominal Watt**

[B] symmetric, wide beam

2700-6000K

24 W






[M] symmetric, medium beam



[E] symmetric, narrow beam

Configurations

| Light distribution | Part ID | Light source | Rated lumens | Rated input power | CRI |
|---|----------|----------------------|--------------|-------------------|-----|
|  <p>[B] symmetric, wide beam</p> | 134-1810 | LED-1/24W/2700-6000K | 1856.5 lm | 24 W | 80 |
|  <p>[E] symmetric, narrow beam</p> | 134-1814 | LED-1/24W/2700-6000K | 946.5 lm | 24 W | 80 |
|  <p>[M] symmetric, medium beam</p> | 134-1812 | LED-1/24W/2700-6000K | 1826.2 lm | 24 W | 80 |