

Description

IP66, Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone rubber gasket. Safety glass lens, hinged. Frame with safety catch. Two cable entries. Intergal ECG control gear in thermally separated compartment. Darklight anodised aluminium reflector, PMMA-Diffuser-Lens for glare control and soft wide beam distribution. Factory-installed LED circuit board.

A pre-installation blackout, proud or flush, is available and recommended for mounting in concrete ceilings. To be ordered separately.

Specifications

Material description

Lens	Safety glass lens, hinged			
Colours	RAL9004 Signal black	RAL9006 White aluminium	RAL9016 Traffic white	RAL7016 Anthracite grey
	RAL9007 Grey aluminium			
Gasket	Silicone rubber gasket			
Fasteners	PCS Polymer Coated Stainless Steel Hardware			
Ingress protection	IP66			
Impact resistance	IK07			
Corrosion resistance	5CE			

Electrical description

Power supply	220-240V / 50-60 Hz
Surge protection	6/6 kV
Energy efficiency	D (Light source)

Additional information

Lifetime	Ta=25° L70B50 > 50000h
----------	------------------------

Options

Light distribution **Colour temperature** **Nominal Watt**



[BD]



3000K




4000K



2700K

24 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [BD]	134-1939	LED-1/24W/2700K	2335.8 lm	24 W	80
	134-1483	LED-1/24W/3000K	2433.8 lm	24 W	80
	134-1484	LED-1/24W/4000K	2537.7 lm	24 W	80