**Description**

IP66, Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Silicone rubber gasket. Safety glass lens, hinged. Frame with safety catch. Two cable entries. Anodised aluminium reflector, PMMA-Diffuser-Lens for glare control and soft wide beam distribution. Intergal ECG control gear in thermally separated compartment.

A pre-installation blackout, proud or flush, is available and recommended for mounting in concrete ceilings. To be ordered separately.

2700 K option available on request.

Specifications

Material description

Lens	Safety glass lens, hinged		
Colours	RAL9004 Signal black	RAL9006 White aluminium	RAL9007 Grey aluminium
Gasket	Silicone rubber gasket		
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)		
Ingress protection	IP66		
Impact resistance	IK07		
Corrosion resistance	5CE+Primer		

Electrical description

Power supply	230V / 50 Hz
Surge protection	6/6 kV
Energy efficiency	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details.

Additional information

Lifetime	Ta=40° L70B50 > 50000h
----------	------------------------

Options


Light distribution **Colour temperature** **Nominal Watt**



[BD]



3000K




4000K



2700K

24 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [BD]	134-1939	LED-1/24W/2700K	2335.8 lm	24 W	80
	134-1483	LED-1/24W/3000K	2433.8 lm	24 W	80
	134-1484	LED-1/24W/4000K	2537.7 lm	24 W	80