

### Description

IP66, Class I. Class II on request. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone rubber gasket. Safety glass lens, hinged. Frame with safety catch. Two cable entries. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board. Optional 2200 K version available. To be specified at time of ordering.

A pre-installation blackout, proud or flush, is available and recommended for mounting in concrete ceilings. To be ordered separately.

Luminaire suitable for chlorine containing environments e.g. swimming pools, on request. Must be specified at time of ordering.

## Specifications

### Material description

Lens	Safety glass lens, hinged			
Colours	<b>RAL9004</b> Signal black	<b>RAL9006</b> White aluminium	<b>RAL9016</b> Traffic white	<b>RAL7016</b> Anthracite grey
	<b>RAL9007</b> Grey aluminium			
Gasket	Silicone rubber gasket			
Fasteners	PCS Polymer Coated Stainless Steel Hardware			
Ingress protection	IP66			
Impact resistance	IK07			
Corrosion resistance	5CE			








### Electrical description

Power supply	220-240V / 50-60 Hz
Surge protection	6/6 kV
Energy efficiency	C-D (Light source)





### Additional information

Lifetime	Ta=25° L90B10 > 90000h
----------	------------------------

**Options****Light distribution**   **Colour temperature**   **Nominal Watt**

	[M]		3000K	24 W
	[EES]		4000K	
	[B]		2700K	
	[EE]			

**Configurations**

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	134-1931	LED-12/24W/2700K	2522.3 lm	24 W	80
	134-1332	LED-12/24W/3000K	2709.2 lm	24 W	80
	134-1333	LED-12/24W/4000K	2896 lm	24 W	80
[B]					
	134-1933	LED-12/24W/2700K	2684.8 lm	24 W	80
	134-1335	LED-12/24W/3000K	2883.7 lm	24 W	80
	134-1335	LED-12/24W/3000K	2883.7 lm	24 W	80
[EE]					
	134-1336	LED-12/24W/4000K	3082.5 lm	24 W	80
	134-1336	LED-12/24W/4000K	3082.5 lm	24 W	80
	134-1934	LED-12/24W/2700K	2865.6 lm	24 W	80
[EES]					
	134-1211	LED-12/24W/3000K	3077.9 lm	24 W	80
	134-1211	LED-12/24W/3000K	3077.9 lm	24 W	80
	134-1213	LED-12/24W/4000K	3290.2 lm	24 W	80
	134-1213	LED-12/24W/4000K	3290.2 lm	24 W	80
	134-1932	LED-12/24W/2700K	2791.8 lm	24 W	80
[M]					
	134-1210	LED-12/24W/3000K	2998.6 lm	24 W	80
	134-1210	LED-12/24W/3000K	2998.6 lm	24 W	80
	134-1212	LED-12/24W/4000K	3205.4 lm	24 W	80
134-1212	LED-12/24W/4000K	3205.4 lm	24 W	80	