

### Description

IP66, Class I. Class II on request. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone rubber gasket. Safety glass lens, hinged. Frame with safety catch. Two cable entries. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board. Gimbal mounted, 30° tiltable and 355° rotatable. Optional 2200 K version available. To be specified at time of ordering.

A pre-installation blockout, proud or flush, is available and recommended for mounting in concrete ceilings. To be ordered separately.

Luminaire suitable for chlorine containing environments e.g. swimming pools, on request. Must be specified at time of ordering.

## Specifications

### Material description

Body	Marine-grade die-cast aluminium alloy			
Lens	Safety glass lens, hinged			
Colours	<b>RAL9004</b> Signal black	<b>RAL9006</b> White aluminium	<b>RAL9016</b> Traffic white	<b>RAL7016</b> Anthracite grey
	<b>RAL9007</b> Grey aluminium			
Gasket	Silicone rubber gasket			
Fasteners	PCS Polymer Coated Stainless Steel Hardware			
Ingress protection	IP66			
Impact resistance	IK07			
Corrosion resistance	5CE			









### Electrical description

Power supply	220-240V / 50-60 Hz
Surge protection	6/6 kV
Energy efficiency	C-D (Light source)






### Additional information

Listings	30° tiltable and 355° rotatable
Lifetime	Ta=25° L90B10 > 90000h

**Options****Light distribution    Colour temperature    Nominal Watt**

	[M]		3000K	18 W
	[EES]		4000K	
	[B]		2700K	
	[EE]			
	[A20]			

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	134-1611	LED-12/18W/3000K	1798.6 lm	18 W	80
	134-1612	LED-12/18W/4000K	1924 lm	18 W	80
[A20]					
	134-1940	LED-12/18W/2700K	1868.4 lm	18 W	80
	134-1344	LED-12/18W/3000K	2008.5 lm	18 W	80
	134-1345	LED-12/18W/4000K	2148.7 lm	18 W	80
[B]					
	134-1942	LED-12/18W/2700K	1988.7 lm	18 W	80
	134-1347	LED-12/18W/3000K	2137.9 lm	18 W	80
	134-1347	LED-12/18W/3000K	2137.9 lm	18 W	80
	134-1348	LED-12/18W/4000K	2287 lm	18 W	80
	134-1348	LED-12/18W/4000K	2287 lm	18 W	80
[EE]					
	134-1943	LED-12/18W/2700K	2122.7 lm	18 W	80
	134-1256	LED-12/18W/3000K	2281.9 lm	18 W	80
	134-1256	LED-12/18W/3000K	2281.9 lm	18 W	80
	134-1257	LED-12/18W/4000K	2441.1 lm	18 W	80
	134-1257	LED-12/18W/4000K	2441.1 lm	18 W	80
[EES]					
	134-1941	LED-12/18W/2700K	2068 lm	18 W	80
	134-1253	LED-12/18W/3000K	2223.1 lm	18 W	80
	134-1253	LED-12/18W/3000K	2223.1 lm	18 W	80
	134-1254	LED-12/18W/4000K	2378.2 lm	18 W	80
	134-1254	LED-12/18W/4000K	2378.2 lm	18 W	80
[M]					