

### Description

IP66, Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Silicone rubber gasket. Safety glass lens, hinged. Frame with safety catch. Two cable entries. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. OLC\_R\_One LED Concept. Factory installed LED circuit board. Gimbal mounted,  $30^{\circ}$  tiltable and  $355^{\circ}$  rotatable.

A pre-installation blackout, proud or flush, is available and recommended for mounting in concrete ceilings. To be ordered separately.

2700 K option available on request. Optional 2200 K version available. To be specified at time of ordering.

## Specifications

### Material description

---

Body	Marine-grade die-cast aluminium alloy						
Lens	Safety glass lens, hinged						
Colours	<table><tr><td><b>RAL9004</b></td><td><b>RAL9006</b></td><td><b>RAL9007</b></td></tr><tr><td>Signal black</td><td>White aluminium</td><td>Grey aluminium</td></tr></table>	<b>RAL9004</b>	<b>RAL9006</b>	<b>RAL9007</b>	Signal black	White aluminium	Grey aluminium
<b>RAL9004</b>	<b>RAL9006</b>	<b>RAL9007</b>					
Signal black	White aluminium	Grey aluminium					
Gasket	Silicone rubber gasket						
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)						
Ingress protection	IP66						
Impact resistance	IK07						
Corrosion resistance	5CE+Primer						

---

### Electrical description

---

Power supply	230V / 50 Hz
Driver / Ballast	Integral EC electronic converter in thermally-separated compartment
Surge protection	6/6 kV
Energy efficiency	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on <a href="http://www.we-ef.com">www.we-ef.com</a> for further details.

---








### Additional information

---





Listings	30° tiltable and 355° rotatable
Lifetime	Ta=40° L90B10 > 90000h

---

**Options****Light distribution    Colour temperature    Nominal Watt**

	[M]		3000K	18 W
	[EES]		4000K	
	[B]		2700K	
	[EE]			

**Configurations**

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	134-1940	LED-12/18W/2700K	1868.4 lm	18 W	80
	134-1344	LED-12/18W/3000K	2008.5 lm	18 W	80
	134-1345	LED-12/18W/4000K	2148.7 lm	18 W	80
[B]					
	134-1942	LED-12/18W/2700K	1988.7 lm	18 W	80
	134-1347	LED-12/18W/3000K	2137.9 lm	18 W	80
	134-1347	LED-12/18W/3000K	2137.9 lm	18 W	80
	134-1348	LED-12/18W/4000K	2287 lm	18 W	80
[EE]					
	134-1348	LED-12/18W/4000K	2287 lm	18 W	80
	134-1943	LED-12/18W/2700K	2122.7 lm	18 W	80
	134-1256	LED-12/18W/3000K	2281.9 lm	18 W	80
	134-1256	LED-12/18W/3000K	2281.9 lm	18 W	80
	134-1257	LED-12/18W/4000K	2441.1 lm	18 W	80
[EES]					
	134-1257	LED-12/18W/4000K	2441.1 lm	18 W	80
	134-1941	LED-12/18W/2700K	2068 lm	18 W	80
	134-1253	LED-12/18W/3000K	2223.1 lm	18 W	80
	134-1253	LED-12/18W/3000K	2223.1 lm	18 W	80
	134-1254	LED-12/18W/4000K	2378.2 lm	18 W	80
[M]					
	134-1254	LED-12/18W/4000K	2378.2 lm	18 W	80