

Description

IP66, Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Silicone rubber gasket. Safety glass lens, hinged. Frame with safety catch. Two cable entries. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. OLC_R_One LED Concept. Factory installed LED circuit board.

A pre-installation blackout, proud or flush, is available and recommended for mounting in concrete ceilings. To be ordered separately.

2700 K option available on request.

Specifications

Material description

Body	Marine-grade die-cast aluminium alloy		
Lens	Safety glass lens, hinged		
Colours	RAL9004 Signal black	RAL9006 White aluminium	RAL9007 Grey aluminium
Gasket	Silicone rubber gasket		
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)		
Ingress protection	IP66		
Impact resistance	IK07		
Corrosion resistance	5CE+Primer		

Electrical description

Power supply	230V / 50 Hz
Driver / Ballast	Integral EC electronic converter in thermally-separated compartment
Surge protection	6/6 kV
Energy efficiency	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details.

Additional information

Lifetime	Ta=40° L90B10 > 90000h
----------	------------------------

Options

Light distribution



[B] symmetric, wide beam



[M] symmetric, medium beam



[EE] symmetric, very narrow beam




[EES] symmetric, very narrow beam, sharp cut-off

Colour temperature



3000K



4000K







2700K

Nominal Watt

48 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	134-1935	LED-24/48W/2700K	5016.9 lm	48 W	80
	134-1396	LED-24/48W/3000K	5388.5 lm	48 W	80
	134-1397	LED-24/48W/4000K	5760.1 lm	48 W	80
[B] symmetric, wide beam					
	134-1401	LED-24/48W/4000K	6398.9 lm	48 W	80
[EE] symmetric, very narrow beam					
	134-1938	LED-24/48W/2700K	5998.4 lm	48 W	80
	134-1402	LED-24/48W/3000K	6442.7 lm	48 W	80
	134-1403	LED-24/48W/4000K	6887 lm	48 W	80
[EES] symmetric, very narrow beam, sharp cut-off					
	134-1936	LED-24/48W/2700K	5630.1 lm	48 W	80
	134-1398	LED-24/48W/3000K	6047.2 lm	48 W	80
	134-1399	LED-24/48W/4000K	6464.2 lm	48 W	80
[M] symmetric, medium beam					