

Description

IP66. Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens, hinged. Two cable entries. CAD-optimized optics for superior illumination and glare control. Integral driver in thermally separated compartment. OLC® One LED Concept. Factory-installed LED circuit board. 0-10V Dimming comes standard with luminaire. Frame with safety catch.

Suitable for installation in non-insulated ceiling. A pre-installation blockout, proud or flush, is available and recommended for mounting in concrete ceilings; to be ordered separately.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)
+ XXX-XXXX (Accessory 1)

Specifications

Material description

Body	Luminaire body and lens frame constructed in die cast aluminum.			
Lens	Clear tempered glass lens.			
Colors	RAL9004 Signal black	RAL9016 Traffic white	RAL8019 Grey brown	RAL9007 Grey aluminium
Gasket	Silicone rubber gasket			
Fasteners	PCS polymer coated stainless steel			
Ingress protection	IP66			
Impact resistance	IK07			
Corrosion resistance	5CE superior corrosion protection system			







Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Integral EC electronic converter in thermally-separated compartment
Surge protection	6/6 kV
Energy efficiency	C-D (Light source)





Additional information

Diameter (inches)	9.84
Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.
Lifetime	Ta=25°/40° L90B10 > 90000h

Options

Light distribution	Color temperature	Nominal Watt
 [B]	 3000K	48 W
 [M]	 4000K	
 [EE]		
 [EES]		

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
	134-1396	LED-24/48W/3000K	5388.5 lm	48 W	80
	134-1397	LED-24/48W/4000K	5760.1 lm	48 W	80
[B]					
	134-1400	LED-24/48W/3000K	5986.1 lm	48 W	80
	134-1400	LED-24/48W/3000K	5986.1 lm	48 W	80
	134-1401	LED-24/48W/4000K	6398.9 lm	48 W	80
	134-1401	LED-24/48W/4000K	6398.9 lm	48 W	80
[EE]					
	134-1402	LED-24/48W/3000K	6442.7 lm	48 W	80
	134-1402	LED-24/48W/3000K	6442.7 lm	48 W	80
	134-1403	LED-24/48W/4000K	6887 lm	48 W	80
	134-1403	LED-24/48W/4000K	6887 lm	48 W	80
[EES]					
	134-1398	LED-24/48W/3000K	6047.2 lm	48 W	80
	134-1398	LED-24/48W/3000K	6047.2 lm	48 W	80
	134-1398	LED-24/48W/3000K	6047.2 lm	48 W	80
	134-1399	LED-24/48W/4000K	6464.2 lm	48 W	80
	134-1399	LED-24/48W/4000K	6464.2 lm	48 W	80
	134-1399	LED-24/48W/4000K	6464.2 lm	48 W	80
[M]					