

Description

IP66. IK08. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Safety glass lens. Silicone CCG[®] Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation.

Integral EC electronic converter in thermally-separated compartment. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control. OLC[®] One LED Concept. Two cable entries.

Pre-installation blockout is recommended for mounting in cast concrete ceilings, available on request.

Specifications

Material description








Body	Marine-grade, die-cast aluminium alloy								
Lens	Safety glass lens								
Colours	<table><tr><td>RAL9004</td><td>RAL9016</td><td>RAL7016</td><td>RAL9007</td></tr><tr><td>Signal black</td><td>Traffic white</td><td>Anthracite grey</td><td>Grey aluminium</td></tr></table>	RAL9004	RAL9016	RAL7016	RAL9007	Signal black	Traffic white	Anthracite grey	Grey aluminium
RAL9004	RAL9016	RAL7016	RAL9007						
Signal black	Traffic white	Anthracite grey	Grey aluminium						
Gasket	Silicone CCG® Controlled Compression Gasket								
Fasteners	PCS hardware								
Corrosion resistance	5CE								

Electrical description





Driver / Ballast	Integral EC electronic converter in thermally-separated compartment
------------------	---

Additional information

Options**Light distribution Colour temperature Nominal Watt**

 [M]	 3000K	24 W 36 W
 [EE]	 4000K	
 [B]	 2700K	
 [EES]		

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [B]	135-9074	LED-12/24W/2700K	2138.3 lm	24 W	80
	135-9058	LED-12/24W/3000K	2296.7 lm	24 W	80
	135-9059	LED-12/24W/4000K	2455 lm	24 W	80
	135-9080	LED-12/36W/2700K	3247 lm	36 W	80
	135-9065	LED-12/36W/3000K	3795.1 lm	36 W	80
	135-9068	LED-12/36W/4000K	3971.6 lm	36 W	80
 [EE]	135-9073	LED-12/24W/2700K	2594.7 lm	24 W	80
	135-9054	LED-12/24W/3000K	2786.9 lm	24 W	80
	135-9057	LED-12/24W/4000K	2979.1 lm	24 W	80
	135-9082	LED-12/36W/2700K	3902.8 lm	36 W	80
	135-9067	LED-12/36W/3000K	4093.2 lm	36 W	80
	135-9070	LED-12/36W/4000K	4283.6 lm	36 W	80
 [EES]	135-9075	LED-12/24W/2700K	2779.9 lm	24 W	80
	135-9060	LED-12/24W/3000K	2985.8 lm	24 W	80
	135-9061	LED-12/24W/4000K	3191.8 lm	24 W	80
 [M]	135-9072	LED-12/24W/2700K	2707.6 lm	24 W	80
	135-9053	LED-12/24W/3000K	2908.1 lm	24 W	80
	135-9056	LED-12/24W/4000K	3108.7 lm	24 W	80
	135-9081	LED-12/36W/2700K	4124.1 lm	36 W	80
	135-9066	LED-12/36W/3000K	4325.2 lm	36 W	80
	135-9069	LED-12/36W/4000K	4526.4 lm	36 W	80