

### Description

IP67. IK09. Stainless steel inground section. Die-cast dome made from marine-grade aluminium alloy. Luminaire can be driven over at low speed. 5CE superior corrosion protection including PCS hardware. Optical lens made from PMMA. Silicone rubber gasket. Factory-sealed termination chamber with cable gland and 1.5 m of flexible PVC-free cable.

Integral EC electronic converter. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept.

Luminaire installation blackout included in supply. Optional 2200 K version available. To be specified at time of ordering.

## Specifications

### Material description

Body	Stainless steel inground section. Die-cast dome made from marine-grade aluminium alloy.			
Colours	<b>RAL9004</b> Signal black	<b>RAL9016</b> Traffic white	<b>RAL7016</b> Anthracite grey	<b>RAL9007</b> Grey aluminium
Gasket	Silicone rubber gasket			
Fasteners	PCS hardware			
Ingress protection	IP67			
Impact resistance	IK09			
Corrosion resistance	5CE			

### Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter
Surge protection	1/2 kV
Energy efficiency	C-D (Light source)

### Additional information

Lifetime	Ta=25° L90B10 > 90000h
----------	------------------------

**Options**


**Light distribution**

[]

**Colour temperature**



3000K



4000K

**Nominal Watt**

6 W

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
[]	185-2526	LED-6/6W/3000K	497 lm	6 W	80
	185-2560	LED-6/6W/4000K	545.1 lm	6 W	80
	185-2559	LED-6/6W/3000K	992.4 lm	6 W	80
	185-2768	LED-6/6W/4000K	1088.4 lm	6 W	80