

Description

IP67, Class I. IK07. Stainless steel construction including PCS hardware. Silicone rubber gasket. Safety glass lens; max. load 5 tonnes. Luminaire can be driven over at low speed. Factory-sealed termination chamber complete with cable gland and 1,5 m of flexible PVC free cable. Cable gland with spiral cable bending protection.

'No tool' removable gear/reflector tray. Anodised aluminium reflector.


Luminaire requires installation blackout and sealable junction box, which are included in supply.

2700 K option available on request.

IMPORTANT! Inground blockouts must be installed with effective drainage, watch [here](https://vimeo.com/672613058).

Specifications

Material description

Body	Stainless steel inground section. Die-cast hood made from marine-grade aluminium alloy		
Lens	Safety glass lens		
Colours	 RAL9004 Signal black	 RAL9006 White aluminium	 RAL9007 Grey aluminium
Gasket	Silicone rubber gasket		
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)		
Ingress protection	IP67		
Impact resistance	IK07		
Corrosion resistance	5CE. 5CE+Primer optional		

Electrical description

Power supply	230V / 50 Hz
Driver / Ballast	Integral EC electronic converter
Termination	Junction box supplied
Energy efficiency	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details.
	Warranty void if installed without proper drainage.

Additional information

Options

Light distribution	Colour temperature	Nominal Watt
 [M]	 3000K	36 W
 [EE]	 4000K	
 [EES]		

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	185-7721	LED-24/36W/3000K	3602.2 lm	36 W	80
	185-7724	LED-24/36W/4000K	3853.5 lm	36 W	80
[EE]					
	185-7722	LED-24/36W/3000K	3788.6 lm	36 W	80
	185-7725	LED-24/36W/4000K	4052.9 lm	36 W	80
[EES]					
	185-7720	LED-24/36W/3000K	3510.1 lm	36 W	80
	185-7723	LED-24/36W/4000K	3755 lm	36 W	80
[M]					