**Description**

IP68. 12 V/Class III. IK09. Stainless steel construction including PCS hardware. Silicone rubber gasket. Safety glass lens. Luminaire can be driven over at low speed. Anti-wick technology, equipped with a cable gland and 1.5 meters of flexible, PVC-free cable. IP68 in-line connector facilitates easy removal for off-site lamp replacement.


Factory installed circuit board with High Efficiency LEDs in either white, red, green, blue or RGB. Mains converter required, to be ordered separately.

Luminaire installation blackout and sealable junction box included in supply.

## Specifications

### Material description

---

Body	Stainless steel construction
Lens	Safety glass lens with opal diffuser, max. load 5 tonnes
Colours	 Stainless Steel
Gasket	Silicone rubber gasket
Fasteners	PCS hardware
Corrosion resistance	5CE

---

### Electrical description

---

Driver / Ballast	[ON-OFF]
------------------	----------

---

### Additional information

**Options**

Light distribution	Colour temperature	Nominal Watt
--------------------	--------------------	--------------

□		4 W
---	--	-----

	W	
--	---	--

	R	
--	---	--

	G	
--	---	--

	B	
--	---	--

	RGB	
--	-----	--

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
[]	185-9560	LED-2/4W/B	0.8 lm	4 W	22
	185-9559	LED-2/4W/G	2 lm	4 W	22
	185-9558	LED-2/4W/R	2.9 lm	4 W	22
	185-9562	LED-3/4W/RGB	3.5 lm	4 W	22
	185-9557	LED-2/4W/W	3.5 lm	4 W	75