

Description


IP69. IK10+. Stainless steel construction including PCS hardware. Safety glass lens; max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 1.5 meters of flexible, PVC-free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept.

Luminaire installation blackout and sealable junction box included in supply.

Specifications

Material description







Body	Stainless steel construction
Lens	Safety glass lens, max. load 5 tonnes
Colours	 Stainless Steel
Gasket	Silicone rubber gasket
Fasteners	PCS hardware

Electrical description





Driver / Ballast	Integral EC electronic converter
------------------	----------------------------------

Additional information

Options**Light distribution Colour temperature Nominal Watt**

 [M]	 3000K	12 W
 [EE]	 4000K	
 [B]		
 [EES]		

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	185-7657	LED-6/12W/3000K	1363.5 lm	12 W	80
	185-7659	LED-6/12W/4000K	1457.5 lm	12 W	80
[B]					
	185-7600	LED-6/12W/3000K	1497 lm	12 W	80
	185-7603	LED-6/12W/4000K	1600.3 lm	12 W	80
[EE]					
	185-7658	LED-6/12W/3000K	1624.7 lm	12 W	80
	185-7660	LED-6/12W/4000K	1736.8 lm	12 W	80
[EES]					
	185-7599	LED-6/12W/3000K	1531.8 lm	12 W	80
	185-7599	LED-6/12W/3000K	1531.8 lm	12 W	80
	185-7602	LED-6/12W/4000K	1637.4 lm	12 W	80
	185-7602	LED-6/12W/4000K	1637.4 lm	12 W	80
[M]					